Yates Petroleum Corporation Lechuguilla Canyon Unit #8 2108' FSL & 1905' FWL Section 10, T24S R24E Eddy County, New Mexico

In conjunction with Form 9-331C, Application for Permit to Drill subject well, Yates Petroleum Corporation submits the following ten items of pertinent information in accordance with USGS requirements:

1. The geologic surface formation is Seven Rivers lime.

2. The estimate tops of geologic markers are as follows:

| Delaware              | 2422' | Strawn          | <b>8</b> 796 <b>'</b> |
|-----------------------|-------|-----------------|-----------------------|
| Bone Spring Limestone | 3320' | Atoka           | 9216'                 |
| 3rd Bone Spring Sand  | 7432' | Morrow Clastics | 9928 <b>'</b>         |
| Wolfcamp              | 7712' | Chester         | 10439'                |
| Lower Canyon          | 8182' | TD              | 10600'                |

3. The estimated depths at which anticipated water, oil, or gas formations are expected to be encountered:

Water: Approximately 150' - 300' 1800' - 2200'

Gas: Strawn - approximately 8800' Atoka - approximately 9230' Morrow - approximately 10000'

4. Proposed Casing Program: See Form 9-331C.

5. Pressure Control Equipment: See Form 9-331C and Exhibit B.

6. Mud Program: See Form 9-331C.

7. Auxiliary Equipment: Kelly Cock; pit level indicators and flow sensor equipment; sub with full-opening valve on floor, drill pipe connection.

8. Testing, Logging and Coring Program:

DST's: As Warranted Logging: Intermediate casing - T.D. Coring: CNL - FDC T.D. to casing with GR-CNL on to surface and DLL from T.D. to casing with selected min. R.O.

9. No abnormal pressures or temperatures are indicated.

10. Anticipated starting date: As soon as possible after approval.