- I. A kelly cock will be installed and maintained in operable condition.

J.

The <u>KIZTES/in</u> Sub-District Office is to be notified in sufficient time for a representative to witness:

- (a) Spudding
- (b) Cementing casing

 inch
 inch
 inch

(c)__<u>BOP_test</u>

Κ.

L.

М.

A Communitization Agreement covering the acreage dedicated to the well must be filed for approval with the U.S. Geological Survey, P.O. Box 26124. Albuquerque, New Maxico 87125. The effective date of the agreement must be prior to any sales.

A Gamma Ray-Compensated Neutron log is required from the base of the salt

section to the surface with cable speed not to exceed 30 feet per minute.



At least one working day prior to constructing the well pad, access roads and/or related facilities, the operator or dirt contractor shall notify the authorized officer (Bureau of Land Management, CARLSBAD area). He shall also notify the Authorized Officer within two working days after completion of earth-moving activities.

N. All access roads constructed in conjunction with the drilling permit (APD) will be limited to a <u>12</u> foot wide driving surface, excluding turnarounds. Surface disturbance associated with construction and/or use of the road will be limited to <u>20</u> feet in width. If well is a producer, all roads will be adequately drained to control runoff and soil erosion. Drainage facilities may include ditches, water bars, culverts and/or any other measures deemed necessary by the authorized officer of the BLM. The following is a general guide for the spacing of water bars:

% Slope

less than	20															200	ft.
2% to $4%$.			•													100	tt.
4% to $5%$.																	
more than									·	•	•	·	•	·	٠	50	ft.
Other spec	ial	S	ti	p.	l l ĉ	it1	0r	1S									



Any permanent pit containing waste oil must be fenced and covered with mesh wire.

5. Re-route Existing road along south-dy of pad C. BARRICHON read where revented, Ser MAP

2

2