Dec. 1973	Budget Bureau No. 42–R1424
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE NM-12391-A
C/SF GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME RECEIVED
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9-331-C for such proposals.)	TONIT AGREEMENT NAME
well well other Par DIE	9. WELL NO. ARTESIA, OFFICE
2. NAME OF OPERATOR Yates Petroleum Corporation	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210	Wildcat And SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	··· ADEA
below.) AT SURFACE: 1630' FSL & 2255' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH     13. STATE       Eddy     NM
5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	, 14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3417' GR
EQUEST FOR APPROVAL TO:       SUBSEQUENT REPORT OF:         EST WATER SHUT-OFF       Image: Subsequent Report of:         RACTURE TREAT       Image: Subsequent Report of:         HOOT OR ACIDIZE       Image: Subsequent Report of:         HOOT OR ACIDIZE       Image: Subsequent Report of:         ULL OR ALTER CASING       Image: Subsequent Report of:         Image: Subsequent Report of:       Image: Subsequent Report of:         Image: Subsequent Report of Subsequent Report report of Subsequent Report Report of Subsequence Report Report of Subsequ	SULVEY CHANGE OF FORM 9-330.)
measured and true vertical depths for all markers and zones pertine pose to plug and abandon well as follows:	directionally drilled, give subsurface locations and ent to this work.)*
measured and true vertical depths for all markers and zones pertine pose to plug and abandon well as follows:	directionally drilled, give subsurface locations and ent to this work.)*
measured and true vertical depths for all markers and zones pertine pose to plug and abandon well as follows: Set CIBP @8500' w/35' cement & spot 30 sx plu Cut 4½" casing @5500' & lay down Spot 30 sx plug across top of 4½" stub	directionally drilled, give subsurface locations and ent to this work.)*
measured and true vertical depths for all markers and zones pertine pose to plug and abandon well as follows: Set CIBP @8500' w/35' cement & spot 30 sx plue Cut 4 <sup>1</sup> <sub>2</sub> " casing @5500' & lay down Spot 30 sx plug across top of 4 <sup>1</sup> <sub>2</sub> " stub Spot 20 sx plug at 3850-3750' Cut 7" casing @2100' & lay down	directionally drilled, give subsurface locations and ent to this work.)*
measured and true vertical depths for all markers and zones pertine pose to plug and abandon well as follows: Set CIBP @8500' w/35' cement & spot 30 sx plu Cut 4 <sup>1</sup> / <sub>2</sub> " casing @5500' & lay down Spot 30 sx plug across top of 4 <sup>1</sup> / <sub>2</sub> " stub Spot 20 sx plug at 3850-3750'	directionally drilled, give subsurface locations and ent to this work.)* lg @7670-75201
measured and true vertical depths for all markers and zones pertine pose to plug and abandon well as follows: Set CIBP @8500' w/35' cement & spot 30 sx plue Cut 4½" casing @5500' & lay down Spot 30 sx plug across top of 4½" stub Spot 20 sx plug at 3850-3750' Cut 7" casing @2100' & lay down Spot 35 sx plug across top of 7" stub Spot 35 sx plug @323-233 in 8-5/8" Spot 10 sx in 8-5/8" at surface & install dry bal approval for plugging was given by Mr. Geo	directionally drilled, give subsurface locations and ent to this work.)* g @7670-7520' r hole marker orge Stewart, USGS, Roswell,
measured and true vertical depths for all markers and zones pertine pose to plug and abandon well as follows: Set CIBP @8500' w/35' cement & spot 30 sx plu Cut 4 <sup>1</sup> / <sub>2</sub> " casing @5500' & lay down Spot 30 sx plug across top of 4 <sup>1</sup> / <sub>2</sub> " stub Spot 20 sx plug at 3850-3750' Cut 7" casing @2100' & lay down Spot 35 sx plug across top of 7" stub Spot 35 sx plug @323-233 in 8-5/8" Spot 10 sx in 8-5/8" at surface & install dry bal approval for plugging was given by Mr. Geo Mr. Eddie Mahfood, Yates Petroleum Corporation	directionally drilled, give subsurface locations and ent to this work.)* g @7670-7520' hole marker orge Stewart, USGS, Roswell,
measured and true vertical depths for all markers and zones pertine pose to plug and abandon well as follows: Set CIBP @8500' w/35' cement & spot 30 sx plue Cut 4 <sup>1</sup> <sub>2</sub> " casing @5500' & lay down Spot 30 sx plug across top of 4 <sup>1</sup> <sub>2</sub> " stub Spot 20 sx plug at 3850-3750' Cut 7" casing @2100' & lay down Spot 35 sx plug across top of 7" stub Spot 35 sx plug @323-233 in 8-5/8" Spot 10 sx in 8-5/8" at surface & install dry bal approval for plugging was given by Mr. Geo Mr. Eddie Mahfood, Yates Petroleum Corporation Subsurface Safety Valve: Manu. and Type	directionally drilled, give subsurface locations and ent to this work.)* g @7670-7520' hole marker orge Stewart, USGS, Roswell,
<pre>measured and true vertical depths for all markers and zones pertine pose to plug and abandon well as follows: Set CIBP @8500' w/35' cement &amp; spot 30 sx plue Cut 4½" casing @5500' &amp; lay down Spot 30 sx plug across top of 4½" stub Spot 20 sx plug at 3850-3750' Cut 7" casing @2100' &amp; lay down Spot 35 sx plug across top of 7" stub Spot 35 sx plug @323-233 in 8-5/8" Spot 10 sx in 8-5/8" at surface &amp; install dry bal approval for plugging was given by Mr. Geo Mr. Eddie Mahfood, Yates Petroleum Corporation Subsurface Safety Valve: Manu. and Type 8. I hereby certify that the foregoing is true and correct</pre>	directionally drilled, give subsurface locations and ent to this work.)* ag @7670-7520' borge Stewart, USGS, Roswell, t. Set @
<pre>measured and true vertical depths for all markers and zones pertine pose to plug and abandon well as follows: Set CIBP @8500' w/35' cement &amp; spot 30 sx plue Cut 4½" casing @5500' &amp; lay down Spot 30 sx plug across top of 4½" stub Spot 20 sx plug at 3850-3750' Cut 7" casing @2100' &amp; lay down Spot 35 sx plug across top of 7" stub Spot 35 sx plug @323-233 in 8-5/8" Spot 10 sx in 8-5/8" at surface &amp; install dry bal approval for plugging was given by Mr. Geo Mr. Eddie Mahfood, Yates Petroleum Corporation Subsurface Safety Valve: Manu. and Type 8. I hereby certify that the foregoing is true and correct</pre>	<pre>directionally drilled, give subsurface locations and ent to this work.)* ig @7670-7520' thole marker orge Stewart, USGS, Roswell,  Set @ Ft. ; Sectydate 10-23-81</pre>
measured and true vertical depths for all markers and zones pertine pose to plug and abandon well as follows: Set CIBP @8500' w/35' cement & spot 30 sx plue Cut 4 <sup>1</sup> <sub>2</sub> " casing @5500' & lay down Spot 30 sx plug across top of 4 <sup>1</sup> <sub>2</sub> " stub Spot 20 sx plug at 3850-3750' Cut 7" casing @2100' & lay down Spot 35 sx plug across top of 7" stub Spot 35 sx plug @323-233 in 8-5/8" Spot 10 sx in 8-5/8" at surface & install dry bal approval for plugging was given by Mr. Geo Mr. Eddie Mahfood, Yates Petroleum Corporation Subsurface Safety Valve: Manu. and Type 8. I hereby certify that the foregoing is true and correct IGNED / (C, A, M,	<pre>directionally drilled, give subsurface locations and ent to this work.)* ig @7670-7520' thole marker orge Stewart, USGS, Roswell,  Set @ Ft. ; Sectydate 10-23-81</pre>
measured and true vertical depths for all markers and zones pertind pose to plug and abandon well as follows: Set CIBP @8500' w/35' cement & spot 30 sx plu Cut 4½" casing @5500' & lay down Spot 30 sx plug across top of 4½" stub Spot 20 sx plug at 3850-3750' Cut 7" casing @2100' & lay down Spot 35 sx plug across top of 7" stub Spot 35 sx plug @323-233 in 8-5/8" Spot 10 sx in 8-5/8" at surface & install dry bal approval for plugging was given by Mr. Geo Mr. Eddie Mahfood, Yates Petroleum Corporation Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct Cut for plugging is true and correct for plugging is true and cor	<pre>directionally drilled, give subsurface locations and ent to this work.)* ig @7670-7520' hole marker orge Stewart, USGS, Roswell,  Set @ Ft. ; Sectydate 10-23-81 office use) }</pre>