

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-12391-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☐ P&A

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)

At surface

1630' FSL &amp; 2255' FWL, Sec. 25-T24S-R23E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3417' GR

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/29/81 - Unset packer & circulated hole w/brine gel. Pulled tubing & packer, set CIBP at 8500' & dumped 35' cement on top of CIBP.

9/30/81 - Cut 4½" casing at 5440' & laid down casing.

10/1/81 - Re-run tubing in hole & set Plug #1 @5489-5309' w/40 sx Class C cement w/CaCl. Tagged plug at 5309'.

10/2/81 - Cut 7" casing @2100' & laid down casing.

10/3/81 - Plug #2 - 3845-3745' w/35 sx Class C cement w/CaCl

Plug #3 - 2150-2050' w/35 sx Class C cement w/CaCl, plug across 7" stub

Plug #4 - 325-225' w/35 sx Class C cement w/CaCl

Plug #5 - Surface plug w/10 sx Class C cement

10/5/81 - Installed dry hole marker. Surface will be restored in accordance w/USGS-BLM requirements. Verbal permission for this plugging was obtained from Mr. George Stewart, USGS, Roswell, by Mr. Eddie Mahfood, Yates Petroleum Corporation.

18. I hereby certify that the foregoing is true and correct

SIGNED Eddie MahfoodTITLE Engineering SecretaryDATE 10-23-81

(This space for Federal or State office use)

APPROVED BY CHIEF, ROSWELL DISTRICT

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: