

Cochell Com #1
1980' FSL, 990' FEL
NE SE Section 30-T23S-R28E
Loving (Morrow) Field
Eddy County, New Mexico

WELL DATA: GL: 3,101' TD: 12,818'
KB: 3,119' PBD: 12,115'

CASING: 16", 65# K-55 set at 454' KB
Cement with 850 sacks class C

10-3/4", 40.5# set at 2,400' KB
Cement with 1800 sacks class C

7-5/8", 29.7# and 33.7# set at 9,680' KB
Cement with 750 sacks

LINER: 5", 23# C-95 set at 12,824' KB
Top of liner at 9,370'
Cement with 420 sacks class H

TUBING: 11,440', 2-3/8" 4.6# N-80 set at 11,440' with
Guiberson double grip wireline packer

EXISTING PERFS: Atoka, 11,524-11,530', 4 SPF

STATUS: Shut-in

PROCEDURE:

1. MIRU completion unit. ND tree, NU BOPD. Kill well, circulate hole clean, TOOH with tubing.
2. RIH with wireline and set 5" CIBP at 11,510' KB. Dump 35' cement on top of plug.
3. RU Wireline and run CBL-GR and cased hole neutron from 8,000-9,000' and 5,000-6,000'.
4. TIH with tubing to 9,000'. Swab well down to 9,000'. TOOH with tubing.
5. Perforate 11,248'-252', 11,312'-322', and 11,328-344' 4 SPF with 3-3/8" casing gun. Correlate to Welex FDC/CNL log run 4/21/81.
6. TIH with tubing and packer or lubricate a packer in on Wireline to 11,200' KB if well flows.
7. Flow test well and acid stimulate if necessary.