C/5F

i Jed /	UNITED STAT		IT IN TRIPLICAT	re- Budget Bureau No. 42 R1424 5. LEASE DESIGNATION AND RESIAL NO.
DEPARTMENT OF THE INTERIOR (Other Instructions on re- GEOLOGICAL SURVEY SUNDRY NOTICES AND DEPORTS ON WELLS			30-026684 .	
			6. IF INDIAN, ALLOTTER OF TRIBE HAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)				
OIL CAS OT	HTR	· · · · · · · · · · · · · · · · · · ·	MAY 4 188 i	7. UNIT AGREEMENT NAME
, NAME OF OPERATOR				8. FARM OR LEASE NAME
Orla Petco, Inc.				Gourley Federal
ADDRESS OF OPERATOR		Ą	27£3 (Froigh	9. WELL NO.
c/o Box 953, Midl and, Texas 79702 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*				5 10. FIRLD AND POOL, OR WILDCAT
See also space 17 below.) At surface 1650' FSL and 1650' FEL				Herradura Bend (Delawara
1620, E2T a	ind 1650' FEL			11. SEC., T., R., M., OR BLK. AND SURVEY OR ARRA
				Sec 31, T-22-S, R-28-E
4. PERMIT NO.	!	whether DF, RT, QR, etc.)		12. COUNTY OR PARISH 13. STATE
	30	56.5 GL		Eddy New Mex
S. Chec	k Appropriate Box To I	ndicate Nature of N	otice, Report, or	Other Data
NOTICE OF	INTENTION TO:	1	SUBS	EQUENT REPORT OF:
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATE	R SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACT	URE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	88007	ring or acidizing	ABANDONMENT
REPAIR WELL	CHANGE PLANS	(Other		its of multiple completion on Well upletion Report and Log form.)
-13-81: Ran 361' of 50 sx to pi	t.	emented with 25	50 sx C1 C,	2% CaCl cemant, circulated
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4	t. casing to a depth 1/2" casing with	emented with 25 ð£~2450'. Tot 500 sx C1 C cem	50 sx C1 C, cal depth of nent, circul	2% CaCl cement, circulated well is 2463'.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8"	t. casing to a depth 1/2" casing with	emented with 25 eff 2450'. Tot 500 sx C1 C cem o a depth of 24	50 sx C1 C, cal depth of nent, circul	2% CaCl cement, circulated well is 2463'.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8"	t. casing to a depth 1/2" casing with tubing and rods t	emented with 25 eff 2450'. Tot 500 sx C1 C cem o a depth of 24	50 sx C1 C, cal depth of nent, circul	2% CaCl cement, circulated well is 2463'.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8"	t. casing to a depth 1/2" casing with tubing and rods t	emented with 25 eff 2450'. Tot 500 sx C1 C cem o a depth of 24	50 sx C1 C, cal depth of nent, circul	2% CaCl cement, circulated well is 2463'.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8"	t. casing to a depth 1/2" casing with tubing and rods t	emented with 25 eff 2450'. Tot 500 sx C1 C cem o a depth of 24	50 sx C1 C, cal depth of nent, circul	2% CaCl cement, circulated well is 2463'.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8"	t. casing to a depth 1/2" casing with tubing and rods t	emented with 25 eff 2450'. Tot 500 sx C1 C cem o a depth of 24	50 sx C1 C, cal depth of nent, circul	2% CaCl cement, circulated well is 2463'.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8"	t. casing to a depth 1/2" casing with tubing and rods t	emented with 25 eff 2450'. Tot 500 sx C1 C cem o a depth of 24	50 sx C1 C, cal depth of nent, circul	2% CaCl cement, circulated well is 2463'.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8"	t. casing to a depth 1/2" casing with tubing and rods t	emented with 25 eff 2450'. Tot 500 sx C1 C cem o a depth of 24	50 sx C1 C, cal depth of nent, circul	2% CaCl cement, circulated well is 2463'.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8"	t. casing to a depth 1/2" casing with tubing and rods t	emented with 25 eff 2450'. Tot 500 sx C1 C cem o a depth of 24	50 sx C1 C, cal depth of nent, circul	2% CaCl cemant, circulated well is 2463'.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8" Waiting on	t. casing to a depth 1/2" casing with tubing and rods t electricity and p	emented with 25 eff 2450'. Tot 500 sx C1 C cem o a depth of 24	50 sx C1 C, cal depth of nent, circul	2% CaCl cement, circulated well is 2463'.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8" Waiting on	t. casing to a depth 1/2" casing with tubing and rods t electricity and p	emented with 25 æf 2450'. Tot 500 sx C1 C cem o a depth of 24 umping unit.	50 sx C1 C, al depth of ment, circul	2% CaCl cement, circulated well is 2463'.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8" Waiting on	t. casing to a depth 1/2" casing with tubing and rods t electricity and p	emented with 25 eff 2450'. Tot 500 sx C1 C cem o a depth of 24	50 sx C1 C, al depth of ment, circul	2% CaCl cement, circulated well is 2463'.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8" Waiting on (This space for Federal A State	casing to a depth 1/2" casing with tubing and rods t electricity and p	emented with 25 of 2450'. Tot 500 sx C1 C cem o a depth of 24 umping unit.	50 sx C1 C, al depth of ment, circul	2% CaCl cemant, circulated well is 2463'. ated.
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8" Waiting on (This space for Federal A State PET	casing to a depth 1/2" casing with tubing and rods telectricity and proceed with the correct with the correc	emented with 25 of 2450'. Tot 500 sx C1 C cem o a depth of 24 umping unit. Agent	50 sx C1 C, al depth of ment, circul	2% CaCl cement, circulated well is 2463'. ated. APP 39 190. DATE 4-27-81
Spud Date: 2-6-81 2-13-81: Ran 361' of 50 sx to pi 3-10-81: Ran 4 1/2" Cemented 4 3-12-81: Ran 2 3/8" Waiting on (This space for Federal A State	casing to a depth 1/2" casing with tubing and rods t electricity and proceeding to the correct True and correct ER W. CHESTER	emented with 25 of 2450'. Tot 500 sx C1 C cem o a depth of 24 umping unit.	50 sx C1 C, al depth of ment, circul	2% CaCl cemant, circulated well is 2463'. ated.