

District I  
PO Box 1980, Hobbs, NM 88241-1980  
District II  
PO Drawer DD, Artesia, NM 88211-0719  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico  
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION  
PO Box 2088  
Santa Fe, NM 87504-2088

Form C-101  
Revised February 21, 1994  
Instructions on back  
Submit to Appropriate District Office  
State Lease - 6 Copies  
Fee Lease - 5 Copies

☒ AMENDED REPORT  
Filed 5/14/93

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address. SDX Resources, Inc. P. O. Box 5061 Midland, TX 79704		GRID Number 020451
Property Code 18172		Property Name State JB Com.
Well No. 1		API Number 30 - 0 15-23514

Surface Location									
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
E	32	23S	28E		1980'	North	660'	West	Eddy

Proposed Bottom Hole Location If Different From Surface									
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
UNDES. Leasing Wildcat - Delaware					Proposed Pool 2				

Work Type Code E	Well Type Code O	Cable/Rotary	Lease Type Code S	Ground Level Elevation GR 3113
Multiple No	Proposed Depth 6125'	Formation Delaware	Contractor N/A	Spud Date Reenter-11/20/95

Proposed Casing and Cement Program					
Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
20"	16"	65#	428'	420 sxs	Surf
14-3/4"	10-3/4"	51#	2444'	2850 sxs	Surf
9-1/2"	7-5/8"	33.7#, 39#	9654'	2150 sxs	3250 Temp Surv.

Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

Amoco cut & pulled 7-5/8" csg @ 2395'. Spotted 70 sxs of cement across cut. Tagged top of plug @ 2212'. See attached Amoco diagram.

Plan to MIRU unit & assemble 10-3/4" x 2-7/8" tbg. head. Drill out surface plug. Drill out 480-513' plug and plug 1593'-1682'. Drill out 70 sx plug to top of 7-5/8" @ 2395'. Test 10-3/4" csg. Cut over & dress off top of 7-5/8" w/mill. Drill out plug in top of 7-5/8" csg & circulate hole clean to 6150'. Pressure test 10-3/4" and 7-5/8". Plan to perforate & squeeze cement from 3100' to top of 7-5/8" @ 2395'.

I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature:

Printed name:

Title:

Date:

11/09/95

Phone:

915-685-1761

OIL CONSERVATION DIVISION

Approved by:

ORIGINAL SIGNED BY TIM W. GUM

Title:

DISTRICT II SUPERVISOR

Approval Date:

11-14-95

Expiration Date:

5-14-96

Conditions of Approval:

Attached ☐

Posted 10-1  
9-27-96  
EXP. INT.