

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 30 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 36 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn 11,180'	T. Kirtland Fruitland	T. Penn. "C"
D. Salt 2000'	T. Atoka 11,421'	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss 12,640'	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Quize
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinberry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand 2552'	T. Entrada	T.
T. Abe	T. Bone Springs 6056'	T. Wingate	T.
T. Wolfcamp 9855'	T. 2nd Bone Spr 7896'	T. Chinle	T.
T. Penn.	T. 3rd " 9150'	T. Permian	T.
T. Cisco (Bough C)	T. T/Morrow 12,024'	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.
No. 2, from.....to.....	feet.
No. 3, from.....to.....	feet.
No. 4, from.....to.....	feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	550	550	Red Beds, Anhydrite				
550	2000	1450	Salt & Anhydrite				
2000	2550	550	Limestone & Anhydrite				
2550	6056	3506	Sandstone & Limestone				
6056	9100	3044	Limestone, Shale & Sandstone				
9100	9830	730	Sandstone				
9830	11180	1350	Shale & Limestone				
11180	11422	242	Limestone				
11422	11550	128	Shale & Sandstone				
11550	12160	610	Limestone, Shale & Chert				
12160	12730	570	Sandstone & Shale				