

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Pogo Producing Company
3. ADDRESS OF OPERATOR
Box 10340 Midland, Texas 79702
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 660' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

- (other) ☐ Run and cement surface pipe

RECEIVED

NOV 28 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

5. LEASE
NM 15433
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
RECEIVED
7. UNIT AGREEMENT NAME
NE Loving DEC 10 1980
8. FARM OR LEASE NAME
NEL "COM" O. C. D.
9. WELL NO.
1 ARTESIA OFFICE
10. FIELD OR WILDCAT NAME
Loving North
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 9, T-23-S, R-28-E
12. COUNTY OR PARISH
Eddy
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3046.4 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/15/80 422' MW 9.2, Vis 35, Bit No. 1 20"
Ran 10 jts (442.42') 16" 65# K-55 STC Csg., shoe @ 441',
FC @ 397.22' centralizers on 1,3, & 5th jts. HOWCO cemented
w/ 510 sxs Lt., 2% CaCl₂, 1/4# flocele per sx., Circ 50 sxs.
Plug down 2:00 am CST 11/15/80. 4 hrs WOC

11/16/80 422' 24 hrs cut off 20" conductor, weld on 16" head, NU

11/17/80 422' Test blind rams to 500 psi, ok; test pipe rams to 500 psi,
ok. Ran 12 1/4" Bit, drilled plug, cement & shoe.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Div. Oper. Mgr. DATE November 25, 1980

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY

TITLE _____

DATE _____

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

DEC 4 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO