

Page 3

7. Method of Handling Waste Disposal - Continued

- D. Current laws and regulations pertaining to the disposal of human waste will be complied with.
- E. Trash, waste paper, garbage and junk will be buried in a separate trash pit and covered with a minimum of 24 inches of dirt. All waste material will be contained to prevent scattering by the wind.
- F. All trash and debris will be buried or removed from the wellsite within 30 days after finishing drilling and/or completion operations.

8. Ancillary Facilities

- A. None needed.

9. Wellsite Layout

- A. The location and dimensions of the well pad, mud pits, reserve pit and location of major rig components are shown on the wellsite layout sketch.
- B. Only minor levelling of the wellsite will be required. No significant cuts and fills will be necessary.
- C. The reserve pit will be plastic lined.

10. Plans for Restoration of the Surface

- A. After completion of drilling and/or completion operations, all equipment and other materials not needed for operations will be removed. Pits will be filled and location cleared of all trash and junk to leave the wellsite in as aesthetically pleasing condition as possible.
- B. Any unguarded pits containing fluids will be fenced until they are filled.
- C. After abandonment of the well, surface restoration will be in accordance with the rehabilitation and/or revegetation requirements of the BLM. This will be accomplished as expeditiously as possible. Barring unforeseen problems, all pits will be filled and levelled within 90 days after abandonment.

11. Other Information

- A. Topography: The location and access road is situated amidst rolling hills and ephemeral water courses. Drainage is toward the east and is tributary to "Dark Canyon". GL elevation is 3328.7'.