

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATE	1
FILE	1
NO. OF COPIES	
NO. OF COPIES	
NO. OF COPIES	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

JUL 14 1981

O. C. D.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR APPLICATIONS TO DRILL OR TO RE-DRILL OR TO PUMP BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.		5a. Indicate Type of Lease State ☒ Fee ☐ 5. State Oil & Gas Lease No. L-6442
OIL WELL ☐ GAS WELL ☒ OTHER ☐ Name of Operator InterNorth, Inc. / Address of Operator 403 Wall Towers West, Midland TX 79701 Location of Well UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM East LINE, SECTION 32 TOWNSHIP 23-S RANGE 31-E NMPH.	7. Unit Agreement Name 8. Farm or Lease Name Poker Lake "32" State 9. Well No. 1 10. Field and Pool, or Wildcat Und. West Sand Dunes (Morrow)	
13. Elevation (Show whether DF, RT, CR, etc.) 3367.5' Gr.	12. County Eddy	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

FROM REMEDIAL WORK ☐ PERMANENTLY ABANDON ☐ CHANGE OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐	REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOB ☐ OTHER Well Completion ☒	ALTERING CASING ☐ PLUG AND ABANDONMENT ☐
---	---	---	--

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1-1-81 Moved in completion rig.
- 3-3-81 Drilled cement out of liner to 14,871' KB.
- 4-4-81 Spotted 6 bbls acid at 14,641-14,303'. Ran cement bond log.
- 8-8-81 Set pkr at 14,369' & perforated w/2 SPF at 14,441-14,457' (36 shots) & 14,469-14,486' (34 shots) 0.50" holes.
- 9-9-81 Acidized perfs w/350 gals Dowell MSR 100. Ran GR log.
- 10-10-81 Treated perfs w/3500 gals 7½% MSR 100, 149,000 SCF N₂.
- 16-16-81 Perforated at 14630.5-14633.5' & 14559-14563' w/4 SPF 0.25" holes (Total 36 shots).
- 19-19-81 Set Otis "J" latch plug in pkr @ 14369', new PBTD.
- 22-22-81 Ran 59 jts (876.49') 2 3/8" 4.7# C-75 DSSHT. 362 jts (11825.54') 2 7/8" 6.5# L-80 EUE; 8 jts (252.7') 2 7/8" 6.5# N-80 EUE. Set tbq w/pkr @ 13972'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

By E. H. Foret E. H. Foret TITLE District Engineer DATE 7-14-81

By W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JUL 20 1981

COPIES OF APPROVAL, IF ANY: