

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator WA Moncrief, Jr		Lease Jurnegan State Com		Well # 1	
Location of Well	Unit 66DN 1980W C	Section 8	Township 24	Range 25	County Eddy
Drilling Contractor To Be Determined		Type of Equipment Rotary ASAP			
* Witness					
APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2"	13 3/8"	48# H40 ST+C		386' 400'	400 SX - Circ
* 11 1/2"	8 5/8"	32# K-55 ST+C		2600'	1000 SX - Circ
7 7/8"	4 1/2"	11.6# N-80 LT+C		11,200'	500 SX -
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____					
Type of Shoe used <u>guide</u> Float collar used <u>yes</u> Btm 3 jts welded <u>yes</u>					
TD of hole 2595' Set 2595' Feet of 8 5/8" Inch 32 # Grade J-55					
New-used csg. @ 2595' with 200 ²⁰⁰ sacks neat cement around shoe					
+ 850 sax BJ HSE additives (10# gels, 1/4# flocc)					
Plug down @ 11845 (AM) (PM) Date 10/9/81					
Cement circulated <u>Yes</u> No. of Sacks 400					
Cemented by BJ Hughes Witnessed by Mike Stullfeld					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					
centralizers @ 2555', 2515', 2475'					
Full returns To TD					