

N.M.C.D. COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other FEB 20 1981
2. NAME OF OPERATOR
Amoco Production Company / O.C.D.
3. ADDRESS OF OPERATOR
P. O. Box 68 Hobbs, NM 88240 ARTESIA, OFFICE
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1650' FWL & 1980' FNL, Sec. 3
AT SURFACE:
AT TOP PROD. INTERVAL: (Unit F, SE/4, NW/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)	<input type="checkbox"/>		<input type="checkbox"/>

5. LEASE
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Federal AD Com.
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Wildcat Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
3-23-28
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3012.4' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

WELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 2-2-81, Moranco Drilling Contractors (Rig #1) spudded a 20" hole at 11:00 a.m. Drilled to a TD of 403' and ran 16" 65# H-40 casing set at 402'. Cemented with 450 SX Class "C" cement with 1% CACL. Plugged down at 11:00 a.m. 2-3-81 and circulated 120 SX cement. Tested casing with 750# for 30 min. and tested OK. Reduced hole to 14-3/4" and resumed drilling.

0+5-USGS, A 1-Hou 1-Susp 1-W. Stafford, Hou 1-Union Oil
1-Read & Stevens 1-Holly Energy 1-GLF

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Gerald L. Frake TITLE Admin. Analyst DATE 2-11-81

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

ACCEPTED FOR RECORD

PETER W. CLESTER

FEB 18 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side