UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Form 9–331 Dec. 1973	Budget Bureau No. 42-R1424	
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME (1)	
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME	
1. oil gas XX	Federal AD Com.	
well — well — other	9. WELL NO.	
2. NAME OF OPERATOR	10. FIELD OR WILDCAT NAME	
Amoco Production Company / 3. ADDRESS OF OPERATOR	Wildcat Morrow	
P. O. Box 68 Hobbs, NM 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	
below.)	3-23-28	
AT SURFACE: 1650' FWL & 1980' FNL, Sec. 3 AT TOP PROD. INTERVAL: (Unit F, SE/4, NW/4)	12. COUNTY OR PARISH 13. STATE Fddv NM	
AT TOTAL DEPTH:	Eddy NM	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	- ATT 110.	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3012.4' GL	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF L. X. FRACTURE TREAT		
SHOOT OR ACIDIZE		
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9~330.)	
PULL OR ALTER CASING	Change on Form 9-330.)	
CHANGE ZONES		
ABANDON*		
(other)		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly starincluding estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertine	directionally drilled, give subsurface locations and	
	₩.	
Drilled to a TD of 2535' and ran 10-3/4" 40.	5# K-55 OO SX Pacesetter Lite with	
casing set at 2535'. Gemented with 200 additives and 275 SX Class "C" cement with a	dditives. Plugged down at	
3:45 p.m. 2-9-81. Circulated 175 SX. WOC 1	8 hrs. and tested casing with	
1000# for 30 min. Tested OK. Reduced hole	to 9-1/2" and resumed drilling.	
0+5-USGS, A 1-Hou 1-Susp 1	-W. Stafford, Hou 1-GLF	
O+5-USGS, A l-Hou l-Susp l l-Union Oil l-Read & Stevens l-Holl		
Subsurface Safety Valve: Manu. and Type	Set @ Ft.	
Japania de Salety Taire, mana, and Type		

المستعدد ويجراها

0+5-USGS 1-Union	· · · · · · · · · · · · · · · · · · ·	ord, Hou	1-GLF
Subsurface Safet	ty Valve: Manu. and Type	Set @) Ft.
l 8. I hereby cerf	tify that the foregoing is true and correct Admin. Analyst DATE		•
APPROVED BY	ACCEPTED FOR RECORD PETER W. CHESTER TITLE DAT	·-	
CONDITIONS OF A	PPROVAL, FEBY 2 5 1981		
	U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO Instructions on Reverse Side		