

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well2. NAME OF OPERATOR
Pogo Producing Company3. ADDRESS OF OPERATOR
P.O. Box 10340 Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 530' FSL & 330' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: 580' FSL & 330' FWL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☒

5. LEASE

NM - 12845

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

SCL Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat - Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 1. T-22-S, R-31-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3550.6'GR 3558.6'KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/07/81: 4562' TD, Well dry, prepare to abandon. RIH to 4522'. HOWCO mixed & spotted 375 sxs C1 C cement w/0.5% CFR-2; POH 29 singles. DP @ 3626' mix & spot 255 sxs C1 C w/0.5% CFR-2. POH 25 jts to 2820', circ 50 sxs cement & spot 225 sxs C1 C w/0.5% CFR-2.

4/08/81: 4562' TD. LD 25 jts DP. DP @ 2036', cement w/225 sxs C1 C w/0.5% CFR-2. POH 29 jts. DP @ 1132', spot 225 sxs C1 C, cement circulated. POH 19 jts to 565'. Spot 230 sxs circulated good. Set 20 sxs top plug. Weld on plate & install dry hole marker. Release rig @ 3:30 pm CST 4/7/81. Plugging operation witnessed by Mr. Coke w/U.S.G.S.

Left 523' of 8 5/8" 24# K-55 csg in hole as surface pipe.

APR 20 1981

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Div. Oper. Mgr. DATE April 16, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 9-4-86
CONDITIONS OF APPROVAL, IF ANY:



RECEIVED

APR 17 1981

**U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO**