

NO. OF COPIES RECEIVED	
DISTRIBUTION	
AMT A FE	
FILE	
U.C.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

SEP 14 1981

O. C. D.  
ARTESIA, OFFICE

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-85

1. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. State Oil & Gas Lease No. L-5386
7. Unit Agreement Name
8. Farm or Lease Name STATE DR
9. Well No. 1
10. Field and Pool, or Wildcat Und. Herradura Bend. Del.
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG (AS TO A DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole
2. Name of Operator CITIES SERVICE COMPANY
3. Address of Operator P. O. Box 1919 Midland, Texas 79702
4. Location of Well UNIT LETTER H 1980 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 36 TOWNSHIP 22S RANGE 27E N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.) 3074.9 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T. D. 2605. Open Hole 346'-2605'. This well was plugged & abandoned in the following manner: RIH w/83 joinst of 2-7/8" tbg. tagged T.D. @ 2604'. Circulated hole w/mud laden fluid.

1. Spotted 35 sx cement plug @ approx. 2604'-2504'.
2. POOH and lay down tbg. to 2377'. Spotted 35 sx of class C neat, cement plug to approx. 2377'-2277', across top of Delaware Ls.
3. Pulled tbg to 1285' & spotted 35 sx plug. Tagged plug @ 1140', across top of Salt @ 1127'.
4. Pulled tbg to 402' & spotted 35 sx plug. Spotted 35 sx plug approx. 402-302 half in-half out of 8-5/8" casing shoe @ 349', tagged plug @ 346'.
5. Laid down remaining tbg. dump 10 sx plug in top of casing.
6. Installed 4" Dry hole marker. Rig Down Unit. Will clean location later.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Elmer Stantz

TITLE Reg. Oper. Mgr.-Prod.

DATE 9-8-81

APPROVED BY Mrs. S. Stantz

TITLE OIL AND GAS INSPECTOR

DATE JAN 8 1982

CONDITIONS OF APPROVAL, IF ANY: