



The blowout preventer assembly shall consist of one single type blind ram preventer, one single type pipe ram preventer, both hydraulically operated, a hydraulic "O" type blowout preventer, valves, choke preventer, and connections, as illustrative. If a tapered drill string is used, a ram preventer must be provided for each size of drill pipe. Casing and tubing rams to fit the preventers are to be available as needed. If correct in size, the flanged outlets of the ram preventer may be used for connecting to the 4-inch I.D. choke flow line and 4-inch I.D. relief line, except when air or gas drilling. All preventer connections are to be open-face flanged.

The blowout preventer assembly shall consist of one single type blind ram preventer, one single type pipe ram preventer, both hydraulically operated, a hydraulic "O" type blowout preventer, valves, choke preventer, and connections, as illustrative. If a tapered drill string is used, a ram preventer must be provided for each size of drill pipe. Casing and tubing rams to fit the preventers are to be available as needed. If correct in size, the flanged outlets of the ram preventer may be used for connecting to the 4-inch I.D. choke flow line and 4-inch I.D. relief line, except when air or gas drilling. All preventer connections are to be open-face flanged.

The blowout preventer assembly shall consist of one single type blind ram preventer, one single type pipe ram preventer, both hydraulically operated, a hydraulic "O" type blowout preventer, valves, choke preventer, and connections, as illustrative. If a tapered drill string is used, a ram preventer must be provided for each size of drill pipe. Casing and tubing runs to fit the preventers are to be available as needed. If correct in size, the flanged outlets of the ram preventer may be used for connecting to the 4-inch I.D. choke flow line and 4-inch I.D. relief line, except when air or gas drilling. All preventer connections are to be open-line flanged.

The blowout preventer assembly shall consist of one single type blind ram preventer, one single type pipe ram preventer, both hydraulically operated, a hydraulic "O" type blowout preventer, valves, choke preventer, and connections, as illustrative. If a tapered drill string is used, a ram preventer must be provided for each size of drill pipe. Casing and tubing runs to fit the preventers are to be available as needed. If correct in size, the flanged outlets of the ram preventer may be used for connecting to the 4-inch I.D. choke flow line and 4-inch I.D. relief line, except when air or gas drilling. All preventer connections are to be open-line flanged.

The blowout preventer assembly shall consist of one single type blind ram preventer, one single type pipe ram preventer, both hydraulically operated, a hydraulic "O" type blowout preventer, valves, choke preventer, and connections, as illustrative. If a tapered drill string is used, a ram preventer must be provided for each size of drill pipe. Casing and tubing runs to fit the preventers are to be available as needed. If correct in size, the flanged outlets of the ram preventer may be used for connecting to the 4-inch I.D. choke flow line and 4-inch I.D. relief line, except when air or gas drilling. All preventer connections are to be open-face flanged.