Form 9-331 Dec. 1973

1. oil

well

below.)

ABANDON*

(other)

N.M.O.C.D. COPY

Form Approved. Budget Bureau No. 42-R1424 UNITED STATES 5. LEASE DEPARTMENT OF THE INTERIOR NM-38463 6. IF INDIAN, ALLOTTEE OR TRIBE NAME RECON GEOLOGICAL SURVEY 7. UNIT AGREEMENT NAME JUL 2 0 1931 SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) 8. FARM OR LEASE NAME 0.00 Pure Gold "B" Federal gas MERCAL CRINES ليا 9. WELL NO. other well 1 2. NAME OF OPERATOR 10. FIELD OR WILDCAT NAME Coquina Oil Corporation Undes. (W. Sand Dunes Morrow) 3. ADDRESS OF OPERATOR 11. SEC., T., R., M., OR BLK. AND SURVEY OR P. O. Drawer 2960, Midland, Texas 79702 AREA 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 Sec. 20-23S-31E AT SURFACE: 660' FSL & 1980' FEL of Sec. 20 12. COUNTY OR PARISH 13. STATE AT TOP PROD. INTERVAL: New Mexico AT TOTAL DEPTH: 14. API NO. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3338' GL SUBSEQUENT REPORT OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF. FRACTURE TREAT SHOOT OR ACIDIZE (NOTE: Report results of multiple completion or zone REPAIR WELL change on Form (4-330.) 111 1 7 198 PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES OIL & GAS U.S. GEOLOGICAL SURVEY Spud Date & Run Casing ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well @ 6:30 p.m. CDT, July 11, 1981.

Drld to 600'. Ran 15 jts

20" csq 94# J-55 STC

600.14

600' Set 0

Cmtd w/800 sx BJ-Lite w/1/4#/sk Cello-Flake and 3% CaCl₂. Tailed w/300 sx Class "C" w/2% CaCl₂. Plug Down @ 2:00 p.m. 7/15/81. firc 100 sx to the pit. WOC 18 hrs. NU Hydril. Test Hydril and csg to 500 psi. o.k. Now drlg ahead.

Subsurface Sat	fety Valve: Manu. and Type			Set @	Ft.
	ertify that the foregoing is true an		ct <u>Drilling Managerbate</u>	July 16, 1981	
APPROVED BY _	ACCEPTED FOR RECOMMIS ROGER A. CHAPMAN APPROVAL, IF ANY: JUL 1 7 1981	1			
	U.S. GEOLOGICAL SURVE ROSWELL, NEW MEXICO	See Inst	tructions on Reverse Side		