N.M.O.C.D. (PY Form 9-331 D c. 1973 UNITED STATES	Form Approved. Budget Bureau No. 42-R1424 5. LEASE	
DEPARTMENT OF THE INTERIOR	NM-38463	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME	
1. oil gas well well other	Pure Gold "B" Federal 9. WELL NO.	
2. NAME OF OPERATOR	1	
Coquina Oil Corporation / 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Undes. (W. Sand Dunes Morrow)	
P. O. Drawer 2960, Midland, Texas 79702 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
below.) AT SURFACE: 660' FSL & 1980' FEL of Sec. 20	Sec. 20 T-23S R-31E 12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Eddy New Mexico	e a la casa da casa da Casa da casa da
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3338 ' GL	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING		
MULTIPLE COMPLETE	1981	
ABANDON* AKISSIA, CH		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, MARCO including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Ran 13-3/8" casing as follows:		
	25101	
70 jts 61# K-55 STC 37 jts 54.5# J-55 STC	1 <u>596'</u>	
Total	4106	
Set @ Cmt'd w/3700 sx BJ Lite w/6% gel, 7#/sk Gilsonite sx Class C w/1% CaCl Circ thru-out job. Displ 7/27/81. Circ 300 sx to pit. Bump plug w/1000 p 13-3/8" casing. Cleaned cement out of casing and 3000. TIH Drill out cement and FC to shoe. Tes Now drilling ahead.	ace w/brine water. PD @ 10:00 p.m., osi. WOC 18 hrs. NU BOP's. Cut off I Hydril. Finish NU BOP's. Test to	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.	
18. I hereby certify that the foregoing is true and correct $\frac{\partial^2 d}{\partial t} = \frac{\partial^2 d}{\partial t}$		
SIGNED Bully M. Price TITLE Drilling Mana		
(This space for Federal or State off ACCEPTED FOR RECORD APPROVED B <u>ROGER A. CHAPMAN</u> CONDITIONS OF APPROVAL, IF ANY:	lice use)	
AUG 4 1981		
U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO	Side	