

Form 9–331 Dec. 1973		Form Approved. Budget Bureau No. 42–R1424
	UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	 5. LEASE NM-15433 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY (Do not use this for reservoir. Use Form	NOTICES AND REPORTS ON WELL m for proposals to drill or toldeepen or plug back to a diff 9-331-C for such proposals.) RECEIVED	erent, H L LOVING
1. oil well	gas die other die dee	NEL MAY 2 2 1981 9. WELL NO.
Y	ucing Company	2 O. C. G. 10. FIELD OR WILDCAT NAME ARTESTA, CARCE
3. ADDRESS OF P.O. Box	AN ESIA OF	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.) AT SURFACE AT TOP PRO	E: 1880' FSL & 760' FEL DD. INTERVAL:	Sec. 9, T-23-S, R-28-E 12. COUNTY OR PARISH Eddy New Mexico
AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.		14. API NO.
	OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3046.4 GR 3055.4 KDB
TEST WATER SH FRACTURE TREA SHOOT OR ACID REPAIR WELL PULL OR ALTER MULTIPLE COMF CHANGE ZONES ABANDON* (other) Run		(NOTE: Report results of multiple completion or zone change on Form 9–330.)
including est measured ar 12/81: TD 2 Devi (437 C1 C @ 4: 13/81: TD 4 C0 c rams	timated date of starting any proposed work. If we ad true vertical depths for all markers and zones pe 45' Finish drilling 12 ¹ / ₄ " hole to ation ¹ / ₂ O at 440'. POOH. Run 11 .71'). Shoe @ 440'. Insert floa w/2% CaCl ₂ and ¹ / ₄ # flocele/sk. C 30 pm MST 5/12/81. WOC 8 hrs. C 40' NU BOP. Test blind rams to 1 ement & drill baffle float from 3	440'. Circ hole clean. Rur survey. jts 8 5/8" 24.0# J-55 ST&C casing t baffle @ 405.91'. Cement w/350 sxs irc 75 sxs cement to surface. CIP ut off casing. Weld on casing head. ,000 psi. Held OK. TIH w/bit #2. 39' to 405'. Test casing and pipe Tested OK. Drilled out shoe jt and
	y Valve: Manu. and Type	Set @ Ft.
	Milliams TITLE Div. Oper.	Mgr May 20, 1981
APPROVED BY CONDITIONS OF A	ACCEPTED FOR RECORD ROGER A. CHAPMAII PPROVAL, IF ANY: JUN 1 1981	
U.I R	S. GEOLOGICAL SURVEY	verse Side U.S. GEOLO 1 1501

.

•