

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR  
Harvey E. Yates

3. ADDRESS OF OPERATOR  
P. O. Box 1933, Roswell, NM 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FSL & 1980' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☒

☐

☐

☐

☐

☐

☐

☐

88210 LEASE  
NM-13628

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Phillips Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME ARTESIA, OFFICE

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 1, T-24S, R-28E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
2963.3

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

MAY 16 1983

01 3 112

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4/27/83 RU Geo Vann, set CIBP @ 6200 w/35' cmt on top. PBTD 6165'. Ran GR-Correlation log test from 4000' back to 3000'. RIH & perf squeeze hole @ 3200'. RIH w/retainer, set @ 750'.

4/28/83 RU Geovann, run GR correlation log from 3750'-2600'.

4/29/83 Run GR Bond log from 3750'-3000'. Showed cmt top @ 3310'. RIH w/perf squeeze holes 3310'. Set retainer @ 3305'.

5/02/83 RU Geo Vann, run CBL & GRCL from 3298 to 2400'. TOC @ 2900'. RIH & perf w/select fire @ 3157, 3168, 3176, 3180, 3187, 3194, 3201, 3281, 3285, 3291, 11 holes 1 SPF.

5/06/83 RU Geo Vann, set CIBP @ 3050' w/30' cmt on top. New PBTD 2980'. Shoot off 4 1/2" csg.

5/07/83 Cut csg @ 2890'. Pull out lay down 71 jts of 4 1/2" csg.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ray T. Fisher TITLE Reservoir Engineer DATE May 12, 1983

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JRP

AUG 25 1983

\*See Instructions on Reverse Side