

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
NM OIL CONS. COMMISSION
Roswell, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 300 FNL X 2600 FEL

AT TOP PROD. INTERVAL: (Unit B, NW/4, NE/4)

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐


MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OR A GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On June 12, 1981, McVay Rig #4 spudded a 17-1/2" hole. Drilled to 410'. Ran 13-3/8", 48#, H-40 surface casing and set at 403'. Cemented with 200 sacks of Class C containing 5#/sack of Gilsonire, 1#/sack of Flocele & 1 % CaCl. Tailed in with 450 sacks of Class C containing 1% CaCl. Did not circulate. Ran 1" to 120' (TCMT). Pumped 25 sacks of Class H with 3% CaCl. WOC 2 hrs. Pumped 25 sacks of Class H with 3% CaCl. WOC 2 hrs. Pumped 62 sacks of Class H with 3% CaCl. Cement circulated to surface. WOC 18 1/2 hrs. Pressure tested casing to 600 psi for 30 min. Tested OK. Reduced hole to 12-1/4" and resumed drilling.

0+4-USGS, R 1-Hou 1-Susp 1-MDR 1-W. Stafford, Hou Set @ _____ Ft.

Subsurface Safety Valve: Make and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Mark R. Chapman TITLE Ast. Adm. Analyst DATE 10-6-81

OCT 7 1981

(This space for Federal or State office use)

APPROVED BY U.S. GEOLOGICAL SURVEY
CONDITIONS OF APPROVAL, IF ANY:
ROSWELL, NEW MEXICO

TITLE _____ DATE _____

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.