

Form C-103  
Revised 12-1-73

|                        |   |
|------------------------|---|
| NO. OF COPIES RECEIVED | 1 |
| DISTRIBUTION           |   |
| SANTA FE               |   |
| FILE                   |   |
| U.S.D.S.               |   |
| LAND OFFICE            |   |
| OPERATOR               |   |

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG HOLE. A. APPLICANT RESERVES THE RIGHT TO USE "APPLICATION FOR PERMIT" (FPM-1) (FPM-1) FOR SUCH PURPOSES.

OIL ☒ WELL      GAB ☐ WELL      OTHER: ☐

Name of Operator

DINERO OPERATING COMPANY

1. Address of Operator

POST OFFICE DRAWER 10505, MIDLAND, TEXAS 79701

#### 4. Location of Well

UNIT LETTER C, 1980 FEET FROM THE West LINE AND 660

THE North LINE, SECTION 10 TOWNSHIP 24-S RANGE 28-E NEAR

15. Elevation (Show whether DF, KF, LR, etc.)

3001.9 G.I.

100-1119

Edel:

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM ALL MEDICAL WORK

TEMPORARILY ABANDON

ADD OR ALTER CABINS

STHFA

PLUG AND ABANDON

### CHANGE PLANS

## GENERAL WORK

CONFERENCE DRILLING OPNS.

CARGING TEST AND CEMENT JOB

1841

ALFIREN, CASSING

PLUS ALL ABANDONMENT

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 6½" hole to 11,778'.

Rar 4½" casing as follows: 3173.32 of 4½-13.50" LT&C  
7495.30 4½-11.60 LT&C Middle  
1149.45 4½-1350 LT&C Top  
Float Collar and Guide Shoe.

Cement by Halliburton with 400 sx. CL. H 5/10% CFR-2 4/10% Halad-22-3# KCL.

Plug down 12:25 P.M. M.S.T. Top of cement outside casing 8400', T.D. inside 11,765'. 2500# to bump plug.

Test casing and Wellhead as we move completion unit on hole.

Release Rotary Rig.

12. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE

DATE

APPROVED BY

TITLE

GATC

CONDITIONS OF APPROVAL, IF ANY: