

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

RECEIVED

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

OCT 13 1981

O. C. D.

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

--

SUNDRY NOTICES AND REPORTS ON WELLS

ARTESIA, OFFICE

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator

Coquina Oil Corporation /

Address of Operator

P. O. Drawer 2960, Midland, Texas 79702

Location of Well

UNIT LETTER J, 1650 FEET FROM THE South LINE AND 1980 FEET FROM  
THE East LINE, SECTION 4 TOWNSHIP 23S RANGE 28E NMPM.

7. Unit Agreement Name

--

8. Farm or Lease Name

Swearingen

9. Well No.

1

10. Field and Pool, or Wildcat  
Undes. North Loving  
Morrow

15. Elevation (Show whether DF, RT, GR, etc.)

3104' GR

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PLUG OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☒  
OTHER Cmt Liner ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 12,750'. Ran 5" liner as follows:

1 Down Jet F/S	1.80'
1 jt 5" N-80 18# FL4S	42.58'
1 5" N-80 ABFL4S 18# Landing & F/C	2.49'
24 jts 5" N-80 18# ABFL4S	996.48'
1 5" 18# MWL Liner Hanger	4.40'
1 5" 18# Tie back sleeve	4.52'
Total	1052.27'

TOL 11,705', Btm Liner 12,748', Tie back sleeve 11,695'. Apprximately 281' overlap.  
Cmt'd with 175 sx C1 "H" w/1% CFR-2 + 5#/sx KC1. PD 11:00 p.m. 10/4/81. WOC 18 hrs.  
Test TOL to 2000 psi for 30 min., o.k. Circ and POOH. Drill 48' hard cmt on top of  
F/C @ 12,705', TOC 12,657'. Test liner to 2000 psi, held o.k.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Sally M. Priole

TITLE Drilling Engineer

DATE October 9, 1981

APPROVED BY W.A. Gressett

TITLE SUPERVISOR, DISTRICT II

DATE OCT 14 1981

CONDITIONS OF APPROVAL, IF ANY: