

For
(Ma.)

N.M.O.C.D. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP. DATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-19842-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "A"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Herradura Bend (Cherry Canyon)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28, T-22-S, R-28-E NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

THE EASTLAND OIL COMPANY

3. ADDRESS OF OPERATOR

P.O. DRAWER 3488 MIDLAND, TEXAS 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1650' FSL and 1730' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3062' GR, 3071' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

Casing setting and test

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in Tinsley and Son Drilling Corp. rotary rig and spudded 15" hole at 11:00 pm, July 11, 1981. Drilled to 360' in anhydrite at 5:30 pm, July 12, 1981. Ran 8 joints 40.5#, 10 3/4" casing, 342', set at 355'. Cemented with 350 sacks Class C, 2% CaCl₂ cement, in place at 12:05 am, July 13, 1981; cement circulated.

Let cement set 18 hours and nipped up BOP. Top of cement in casing at 325'. Tested casing and BOP with 600 psi for 30 minutes with no leakoff. Drilled ahead at 9:00 am, July 14, 1981 with 7 7/8" bit and brine water for mud.

RECEIVED
JUL 21 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Vice President Production

DATE

July 17, 1981

(This space for Federal or State Record)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

ROGER A. CHAPMAN

TITLE

DATE

JUL 28 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.