

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. This form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "D" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
D. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Ortiz _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinberry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todillo _____	T. _____
T. Drinkard _____	T. Delaware Sand <u>2300-1</u>	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs <u>6000-5</u>	T. Wingate _____	T. _____
T. Wolfcamp _____	T. <u>Lamar (2) 3500</u>	T. Chinle _____	T. _____
T. Penn. _____	T. <u>Cherry Canyon-3</u>	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. <u>Brushy Canyon-4</u>	T. Penn. "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from <u>2300</u> to <u>2500</u>	No. 4, from <u>4200</u> to <u>5600</u>
No. 2, from <u>3500</u> to <u>3550</u>	No. 5, from <u>6000</u> to <u>9200</u>
No. 3, from <u>3600</u> to <u>4200</u>	No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from <u>200</u> to <u>300</u> feet
No. 2, from _____ to _____ feet
No. 3, from _____ to _____ feet
No. 4, from _____ to _____ feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	200	200	Sand & Rock Gravel				
200	450	250	Redbed				
450	2300	1850	Anhy.				
3500	3550	50	Lamar				
3600	4200	600	Cherry Canyon				
4200	5600	1400	Brushy Canyon				
6000	9200	3200	Bone Spring				