- F. All trash and debris will be buried or removed from the wellsite within 30 days after finishing each drilling and/or completion operation.
- 8. ANCILLARY FACILITIES: None anticipated.

## 9. WELLSITE LAYOUT:

- A. The wellsite has been surveyed and a  $500' \times 400'$  area has been staked and flagged.
- B. The dimensions and relative location of the drill pad, mud pit, and trash pit with respect to the well bore are shown on Exhibit "D".
- C. The location is nearly level and will hardly require any cut or fill.
- D. The well pad will be surfaced with caliche.

## 10. PLANS FOR RESTORATION OF THE SURFACE:

- A. After completion of drilling and/or completion operations, all equipment and other material not needed for operations will be removed. Pits will be filled and the location cleaned of all trash and junk to leave the wellsite in as aesthetically pleasing condition as possible.
- B. Any unguarded pits containing fluids will be fenced until they are filled.
- C. After abandonment, all equipment, trash and junk will be removed and the location cleaned. Any special rehabilitation and/or special revegetation requirements of the Bureau of Land Management will be complied with and accomplished as expeditiously as possible.

## 11. OTHER INFORMATION:

- A. Topography: The undisturbed wellsite elevation is 3082 feet. The surface of the location is nearly level. The terrain of the area surrounding the location slopes to the southwest toward the Pecos River.
- B. Soil: Top soil at the wellsite is loam.