	handa re	1	
· <del></del>	EII, A1	· <del> </del>	
Submit 3 Copies	Land Office		
to Appropriate	सावस		
District Office	Operator		

## State of New Mexico Energy, Minerals and Natural Resources Department



DEC 2 7 1990

Revised 1-1-89 DISTRICTH OIL CONSERVATION DIVISION P.O. Box 2008 P.O. Box 1980, 11066s, NM 83240 WELL API NO. Santa Fe, New Mexico 87504-2088 30-015-23910 P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease DEC 27 '90 FEE XX STATE 1000 Rio Brazos Rd., Aziec, NM 87410 6. State Oil & Gas Lease No. SUNDRY NOTICES AND REPORTS ON WELLSE, OFFICE ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" 7. Lease Name or Unit Agreement Name (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: SAO WEIJ, OGDEN ۸gr X 2. Name of Operator Bird Creek Resources, Inc. 8. Well No. Address of Operator 810 S. Cincinnati, Suite 110, Tulsa, Ok 9. Pool name or Wildeat 74.119 Well Location Wildcat Delaware Unit Letter A : 430 Feet From The North Line and 550 Feet From The East Section thip 245 Range 28E

10. Elevation (Show whether DF, RKB, RT, GR, etc.) Township 245 NMPM County 3064' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORABILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CASING TEST AND CEMENT JOB STHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed Spud 7 7/8" reentry hole on 12-10-90 w/ Pride Unit. Drilled cmt. plug @ 0-65', fell free. Drilled cmt. plug @ 305-511', fell free. Drilled cmt. plug @ 2298-2475', fell free (8 5/8" shoe @ 2403'). Lowered bit, drilled cmt. plug @ 2805-2860' to top of 4 1/2" csg. TOH w/ bit. TIH w/ overshot and flat-bottom mill to 2860'. Milled to 2865', some metal returns. TOH. TIH w/ impression block, showed splintered csg. looking up, enlarged to 6 1/2". TIH w/ open-ended workstring to 2865'. On 12-17-90, by Western Co., set 50 sxs. "C" and 2% CaCl @ 2865-2744'. Spotted 10.2# brine mud 2665-1400'. TOH w/ tbg. NDBOP. NU wellhead. RDPU. SI well and evaluate to sidetrack junk and drill new 7 7/8" hole. I hereby certify that the information above is true and complete to the best of my knowledge and belief. ...... anti ...... \_Agent TOTE OR PRINT NAME Bill M. Burks 918-582-3855 (This space for State Use) ORIGINAL SIGNED BY

ATTROVED BY -

MIKE WILLIAMS

SUPERVISOR, DISTRICT IT