

INSTRUCTIONS

This form is to be filed with the district office of the Commission not later than 30 days after the completion of any newly-drilled or deepened well. It shall be accompanied by a copy of a log of the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured by tape. In the case of fire-shaftly drilled wells, true vertical depths shall also be reported. For multiple completions, items 3b through 3d shall be reported for each zone. The form is to be filed in duplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Ashby <u>675'</u>	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka <u>11172</u>	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Qtzite
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinberry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand <u>2368</u>	T. Entrada	T.
T. Abo	T. Bone Springs <u>5770</u>	T. Wingate	T.
T. Wolfcamp <u>9051</u>	T. Morrow <u>11800</u>	T. Chinle	T.
T. Penn.	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from <u>11172</u> to <u>11383</u>	No. 4, from _____ to _____
No. 2, from <u>5770</u> to <u>8717</u>	No. 5, from _____ to _____
No. 3, from _____ to _____	No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	40	40	Quaternary sand & gravel	7330	7630	300	Sand, shale & lime.
40	675	637	Triassic Red Beds	7630	8100	470	Lime & shale.
675	1420	745	Andydrite	8100	8190	90	Sand, lime & shale.
1420	2330	910	Andydrite & salt	8190	8230	40	Sand, lime & shale.
2330	2870	540	Sand & shale	8230	8270	40	Shale, lime & chert.
2870	3000	130	Sand, lime & chert	8270	8700	430	Lime & shale.
3000	3170	170	Sand & shale	8700	9370	670	Sand lime & shale.
3170	3430	260	Sand & lime	9370	10000	630	Lime & shale.
3430	5770	2340	Sand shale & lime	10000	10130	130	Lime, shale & chert.
5770	5900	130	Shale & lime	10130	10240	110	Lime & shale.
5900	5930	30	Sand, lime & shale	10240	11220	980	Shale & lime.
5930	6830	900	Lime & shale	11220	11870	650	Lime, shale & chert.
6830	7060	230	Sand & shale	11870	12003	133	Lime, sand & shale.
7060	7330	270	Lime & shale				