

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well
2. NAME OF OPERATOR
PERRY R. EASS
3. ADDRESS OF OPERATOR
P.O. Box 2760, MIDLAND, TX 79702 - 2760
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL 660 FWL SEC 18, T22S, R29E,
AT TOP PROD. INTERVAL: UNIT LETTER K.
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
 FRACTURE TREAT ☐
 SHOOT OR ACIDIZE ☐
 REPAIR WELL ☐
 PULL OR ALTER CASING ☐
 MULTIPLE COMPLETE ☐
 CHANGE ZONES ☐
 ABANDON* ☐
 (other) *SPUD 15" HOLE*

(other) SP4D 15" HX E

SUBSEQUENT REPORT OF:

- | | | | | | | | |
|---|--|--|--|--|--|--|--|
| 5 | | | | | | | |
|---|--|--|--|--|--|--|--|

RECEIVED
(NOTE: Report to be filed in the file)
JAN 12 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SPUDDED 4:00 AM 1-5-82,
DRILLED 15" HOLE TO 350'
RAN (9 JTS.) 11 3/4" 42* H-40 STC CS6.
400 SKS CL "C" + 2% CACIZ (14.8 PPB, 1.32 FT³ SK)
PULG DOWN @ 4:30 PM CTS 1-5-82 CIRC 150 SKS
WOC. 26 HRS.
1-7-82 DRILLING 11" HOLE.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

- 18. I hereby certify that the foregoing is true and correct**

SIGNED *K. L. Hartman* (S)

TITLE *Prod. Clerk*

DATE JAN-11-1982

THOMAS A. CRITCHFIELD

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL IF ANY: _____

TITLE

DATE _____

U.S. GEOLOGICAL SURVEY

*See Instructions on Reverse Side