

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
FERRY R. BASS
3. ADDRESS OF OPERATOR
Box 2760, MIDLAND, TX 79702-2760
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL; 660' FWL SEC. 18 T22S R24E
AT TOP PROD. INTERVAL: UNIT L
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	☐	☐
FRACTURE TREAT	☐	☐
SHOOT OR ACIDIZE	☐	☐
REPAIR WELL	☐	☐
PULL OR ALTER CASING	☐	☐
MULTIPLE COMPLETE	☐	☐
CHANGE ZONES	☐	☐
ABANDON*	☐	☒

(other) CORE #1, LOGGING, DST #1, PCA,

5. LEASE
VM 03302
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
RECEIVED
7. UNIT AGREEMENT NAME
BIG EDDY UNIT
8. FARM OR LEASE NAME
BIG EDDY UNIT
9. WELL NO.
88
10. FIELD OR WILDCAT NAME
EDDY UNDESIGNATED
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 18 T22S R29E
12. COUNTY OR PARISH
EDDY
13. STATE
NEW MEXICO
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3249.9' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

DRLG. 7 7/8" HOLE TO 12,666, 2-21-82.
CORE #1 FROM 12,666 TO 12,691 25' CORE RECOVERY 23'
USED CHRISTENSEN MC-40 7 2 3/32 & 4.
DRLG. 7 7/8" HOLE TO 13,060' 2-27-82 LOGGING RAN FSL-CNL-FIL
DLL-MSFL-FIL. 3-1-82 PLUG BACK TO TEST
MIDDLE MUDROW. 12,145' SPOT 80 SKS CLASS "H" NEAT (16.1 PP9)
1.08 CY. FT/SK.) @ 12,894' PB 12,762' TAGGED TOP OF CEMENT
@ 12,745' DST #1 12,410 TO 12,762' (352') M. MUDROW OPEN 5 MIN.
WEAK BLOW 1 1/2" IN BUCKET ST 50 MIN. OPEN 60 MIN. VERY WEAK BLOW
S.F 120 MIN. RECOVERED 360' MUD, BHT 204 F 1 HP 777 PSI OVER

Subsurface Safety Valve: Manu. and Type N/A Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R.C. Hartmann TITLE PRODUCTION CLERK DATE MARCH 23, 1982

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY CU
CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE

APR 16 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

1 FHP 157-175 PSI 151P 3363 PSI FHP 230-248 PSI K-SIP 2873 PSI

FHP 7736 PSI. 3-4-82. PLAN TO PEA.

PLUG # 1 70 SXS CLASS "H" NEAT W/ ADDITIVES @ 13,179'-11,952' 6 DBLS BACKFLOW.

PLUG # 2 70 SXS. CLASS "H" CEMENT { @ 11,687'-11,479'

PLUG # 3 60 SXS. CLASS "H" CEMENT { @ 9,970'-9,810'

PLUG # 4 60 SXS. CLASS "H" CEMENT { @ 6,605'-6,500'

TAGGED CEMENT @ 6538'

PLUG # 5 50 SXS. CLASS "H" CEMENT W/ ADDITIVES @ 3030'

PLUG # 6 30 SXS. CLASS "H" NEAT @ 398'

SET SURFACE PLUG @ 50' W/ 15 SXS. CLASS "H" NEAT @ SURFACE.

WELL PEA 3-6-82. RIG RELEASED @ 5:00 AM.