

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
Artesia, NM 88210

SUBMIT IN DUPLICATE

Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL:		OIL WELL ☐	GAS WELL ☒	DRY ☐	Other ☐		
b. TYPE OF COMPLETION:		NEW WELL ☒	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☐	DIFF. RESVR. ☐	Other ☐
2. NAME OF OPERATOR						OCT 22 1982	
Coquina Oil Corporation							
3. ADDRESS OF OPERATOR						O. C. D.	
P. O. Drawer 2960, Midland, Texas 79702						ARTESIA OFFICE	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*							
At surface 660' FSL & 1980' FWL							
At top prod. interval reported below							
At total depth Same							
14. PERMIT NO.				DATE ISSUED			
				11/16/81			
15. DATE SPUDDED				19. ELEV. CASINGHEAD			
1/31/82				--			
16. DATE T.D. REACHED				19. ELEV. CASINGHEAD			
7/21/82				--			
17. DATE COMPL. (Ready to prod.)				19. ELEV. CASINGHEAD			
9/28/82				--			
18. ELEVATIONS (DF, REB, RT, GR, ETC.)*		19. ELEV. CASINGHEAD		19. ELEV. CASINGHEAD			
3327' GL		--		--			
20. TOTAL DEPTH, MD & TVD		21. PLUG, BACK T.D., MD & TVD		22. IF MULTIPLE COMPL., HOW MANY*			
14,850'		14,521'		--			
23. INTERVALS DRILLED BY		24. INTERVALS DRILLED BY		25. WAS DIRECTIONAL SURVEY MADE			
0-14,850'		--		No			
26. TYPE ELECTRIC AND OTHER LOGS RUN		27. WAS WELL CORED		27. WAS WELL CORED			
CNL/FDC, DLL/MSFL, BHC		No		No			
28. CASING RECORD (Report all strings set in well)							
CASING SIZE		WEIGHT, LB./FT.		DEPTH SET (MD)			
20"		94#		604'			
13-3/8"		61 & 54.5#		4132'			
9-5/8"		47#		12,402'			
HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED			
26"		800 sx Lite, 350 sx C1 C					
17 1/2"		4000 sx Lite 300 sx C1 C					
12 1/4"		1st Stg: 1700 sx Lite, 400 sx C1 H					
		2nd Stg: 350 sx C1 H, 150 sx C1 C					
29. LINER RECORD							
SIZE		TOP (MD)		BOTTOM (MD)			
7-5/8"		11,977'		14,247'			
5"		14,053'		14,849'			
SACKS CEMENT*		SCREEN (MD)		30. TUBING RECORD			
400				SIZE			
160				2-7/8"			
				DEPTH SET (MD)			
				14,181'			
				PACKER SET (MD)			
				14,150			
31. PERFORATION RECORD (Interval, size and number)							
14,348-361', 4", 14 shots 14,266-280', 4"							
14,338-342', 4", 5 shots 5 shots							
14,325-336', 4", 12 shots							
14,312-322', 4", 11 shots							
14,296-306', 4", 11 shots							
14,284-292', 4", 9 shots							
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.							
DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED					
14,266'-361'		7000 gal MS Acid, 1000 Ft ³ /Bbl					
		Nitrogen. 59 Bbl 2% KCl w/1000					
		SCF/Bbl N ₂ .					
33. PRODUCTION							
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)		WELL STATUS (Producing or shut-in)			
N/A		Flowing		SI			
DATE OF TEST		HOURS TESTED		CHOKE SIZE			
9/28/82		5 1/2		Various			
PROD'N. FOR TEST PERIOD		OIL—BBL.		GAS—MCF.			
		None		703			
WATER—BBL.		GAS—OIL RATIO					
7.5		N/A					
FLOW. TUBING PRESS.		CASING PRESSURE		CALCULATED 24-HOUR RATE			
Various		0		0			
OIL—BBL.		GAS—MCF.		WATER—BBL.			
CAOF 15,633		32.7		N/A			
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)							
Flared							
35. LIST OF ATTACHMENTS							
CNL/FDC, DLL/MSFL, BHC, DST #1, 2, 3 & 4							
36. I hereby certify that the foregoing and attached information is complete and correct, as determined from all available records.							
SIGNED		TITLE		U.S. GEOLOGICAL SURVEY			
Sally M. Riche		Operations Superintendent		ROSWELL, NEW MEXICO			

* (See Instructions and Spaces for Additional Data on Reverse Side)
ROSWELL, NEW MEXICO

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. **Items 22 and 24:** If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES			38. GEOLOGIC MARKERS			
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Base Salt	3390'					
Delaware Mtn Grp	4055'					
Cherry Canyon	4920'					
Brushy Canyon	6230'					
Bone Springs	7925'					
1st Bone Spr Sd	8305'					
2nd Bone Spr Sd	8935'					
3rd Bone Spr Sd	10,730'					
Wolfcamp	11,225'					
Strawn	12,930'					
Atoka	13,199'					
Morrow	13,766'					
Lower Morrow	14,637'					
Barnett	14,748'					