

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

Supersedes Old
C-102 and C-103
Effective 1-1-65

JUL 7 1982

30-015-24013

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease
State ☐ Fee ☐

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL OR RE-ENTER FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☒ OTHER ☐ *RA*

Name of Operator
InterNorth, Inc.

Address of Operator
403 Wall Towers West, Midland TX 79701

Location of Well
UNIT LETTER I 1980 FEET FROM THE South LINE AND 660 FEET FROM
THE East LINE, SECTION 19 TOWNSHIP 24-S RANGE 28-E N.M.P.M.

7. Unit Agreement Name

6. Farm or Lease Name
Pardue "19" Com.

9. Well No.
1

10. Field and Pool, or Wildcat
Wildcat (Morrow)

11. Elevation (Show whether DF, RT, CR, etc.)
3078.6' Gr.

12. County
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☐

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-22-82. Rigged up Wellex. Set 5" CIBP at 12,390' and dump-bailed 3-1/2 sx. cmt. on top (35'). Set 5" CIBP at 12050' and dump-bailed 3-1/2 sx. cmt. on top (35'). Set 7-5/8" CIBP at 9980' (top of 5" liner) and dump-bailed 9 sx. cmt. on top (36').

6-24-82. Ran CBL and found top of cmt. at 3250'.

6-25-82. WIH open ended to 5050'. Set 100' cmt. plug (25 sx.) across DV tool (5001') from 4950' to 5050'. Perforated 7-5/8" csg. from 2399' to 2401' w/2 shots/ft. (4 holes). WIH w/Howco cmt. retainer and set at 2360'. Established circulation between 7-5/8" and 10-3/4" csg. Squeezed out 59 sx. below retainer. POOH and layed down tbg. Spotted 15 sx. cmt. (57') in top of csg.

6-26-82. Removed wellhead and installed dry hole marker. Well Plugged and abandoned.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E.H. Foret E.H. Foret TITLE District Engineer DATE 6-30-82

APPROVED BY Mike Stubblefield TITLE OIL AND GAS INSPECTOR DATE OCT - 5 1982

CONDITIONS OF APPROVAL, IF ANY: