

RIG R.D. 25

DRAWWORKS:

National 80-B (1,000 H.P.) Drum Grooved for 1 1/4" line Baylor Model 6032 Brake Satellite Drilling Control Crown-o-Matic Equipped

DRIVE GROUP:

National - BT-24P-1 1/2 Quad

POWER:

- 3 Caterpillar D-379 TA Diesel Engines Rated at 1835 H.P. Hoisting — 1560 H.P. Pumping and Drilling, Complete with National C245-125 Torque Converters
- 2 Caterpillar D-3412; 320 K.W. A.C. Sets -- 230/460 volts

PUMPS:

2 - National 9P100 (1,000 H.P.) each with 5 x 6 Mission Magnum Centrifugal Charging Pump Driven by 60 H.P. Motor

MAST:

142' x 21' Derrick Service Inter, 6 Sheave 430 ton Crown Block

720,000 lb. A.P.I. Static Hook Load Capacity with 10 lines

SUBSTRUCTURE:

DSI 21 foot High

700,000 lb. Casing Capacity Simultaneous with 500,000

TRAVELING BLOCK AND HOOK:

National 545G350 Hook-Block (350 ton)

SWIVEL:

National P-400 (400 ton)

ROTARY:

National C-275 (500 ton) 27 1/2" Opening Complete with Kelly Bushing Guard

DRILL STRING:

5 1/4" x 40' Hex Kelly

10,000' - 4 1/2" 16.60 lb., Range II, Grade E with 6 1/4" O.D. Tool Joints

4,000' - 4 1/2" 16.60 lb., Range II, Grade G with 6 1/4" O.D. Tool Joints

BLOWOUT PREVENTERS AND CONTROLS:

- 1 13 5/8" 5,000 lb. W.P. Cameron Type "D" Annular for H₂S Service
- 2 13 5/8" 5,000 lb. W.P. Cameron Type "U" Single for H₂S Service
- 5,000 lb. W.P. Choke and Kill Manifold for H₂S Service (Type "F" Hydraulic Operated Gate Valve)
- 1 Koomey 5 Station Closing Unit with 180 Gallon Accumulator Complete with Remote Closing Unit

MUD SYSTEM:

3 - 7' x 10' x 38' Mud Tanks (1160 bbl. Useable Capacity) Swaco Model 212 Desander (1000 GPM) Swaco Model 6T4 Desilter (900 GPM) Brandt High Speed Dual-Tandem Shale Shaker Mud Mixing Unit with Mud Hopper, Manifold and 2 - 6 x 8 Mission Magnum Centrifugal Pumps each Driven by 75 H.P. Motor

- 4 Brandt Model MA10 Mud Agitators
- 1 5 x 6 Mission Magnum Desander Pump Driven by 60 H.P. Motor
- 1 5 x 6 Mission Magnum Desilter Pump Driven by 60 H.P. Motor

Mud-Gas Separator

AUXILIARY EQUIPMENT:

International Tool Kelly Spinner Varco Power Slips, Model PS15 Spinner Hawk Drill Pipe Wrench Zip-Lift Drill Collar System Explosion Proof Lighting

- 2 Quincy Model 5120 Air Compressors, 84 C.F.M. at 115 P.S.I. each Driven by 20 H.P. Motor
- 2 2 x 3 Mission Magnum Centrifugal Water Pumps each Driven by 25 H.P. Motor
- 10' x 45' Combination Office and Toolpusher Quarters with Galley

Air Hoist

12,000 Gallon Fuel Tank with 5 Compartment Lubster Totco Weight Indicator Complete with Pump Pressure, Pump Stroke, Rotary RPM, Rotary Torque and Tong Torque Systems