

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-24061
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Cass Draw
8. Well No. 1
9. Pool name or Wildcat Loving Morrow North
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3087.4' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator Read & Stevens, Inc.
3. Address of Operator P. O. Box 1518 Roswell, NM 88201
4. Well Location Unit Letter I : 1980 Feet From The South Line and 990 Feet From The East Line Section 24 Township 23S Range 27E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Read & Stevens, Inc. proposes to plug and abandon the subject well according to the procedure below.

Set CIBP @ 11,350' (top of the Atoka) and cap w/ 50' cmt. Set 150' cmt plug inside and outside top of 5" liner @ 9,004'. Set 150' cmt plug @ 6,500' (top first Bone Spring sand). Cut and pull 7 5/8" csg from 4,000' (TOC @ 4,550'). Set 100' cmt plug in and out of the 7 5/8" csg stub. Set 100' cmt plug in and out of 10 3/4" csg shoe @ 2,438'. Set 100' cmt plug in and out of 16" csg shoe @ 400'. Set 50' cmt plug @ surface. Install dry hole marker and clean and level location. Cmt will be displaced and hole circulated w/ mud laden fluid.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John C. Maxey, Jr. TITLE Petroleum Engineer DATE 12-22-93
TYPE OR PRINT NAME John C. Maxey, Jr. TELEPHONE NO.

(This space for State Use)

APPROVED BY [Signature] TITLE Field Rep DATE 1/20/94

CONDITIONS OF APPROVAL, IF ANY:

* Plug 3087.4' GR
* Plug 3087.4' GR
* Plug 3087.4' GR

Plugging