

Alameda, NM 88210

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

CASF

SUNDRY NOTICES AND REPORTS ON WELLS


(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well ☐ well ☐
2. NAME OF OPERATOR
~~BASS ENTERPRISES PROD CO. P.O. Box 1, Roswell, NM~~
3. ADDRESS OF OPERATOR
BOX 2760, MIDLAND, TX 79702-2760
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1440' FWL & 860' FWL SEC 6 T23 S 31 E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: 1787' FSL & 860' FWL SEC 31 T23 S 31 E
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) SPUD & SURFACE CSB.

SUBSEQUENT REPORT OF:



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SPUD 2:30 AM 2-6-82
DRUG. 17 1/2" HOLE TO 500'
RAN 13 JTS. 13 3/8" 48# H-40 STEEL CSG. SET @ 500'
CEMENT W/650 SX CLASS "C" W/ADDITIVES, CIRC 300 SX
BUMPED PLUG TO 650 PSI. PLUG DOWN @ 7:25 PM CST 2-7-82
FLOAT HELD. WOC 24 1/4 HRS. ARLIN COKE W/USBS WAS PRESENT
2-9-82 COMMENCED DRUG. 12 1/4" HOLE.

Subsurface Safety Valve: Manu. and Type

Set @ Ft

18. I hereby certify that foregoing is true and correct

SIGNATURE ROGER A. CHAPMAN

TITLE PRODUCTION CLERK DATE 2-17-82

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY

FEB 23 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO