

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other
2. NAME OF OPERATOR Perry R. Bass
~~BASS ENTERPRISES PRODUCTION CO.~~
3. ADDRESS OF OPERATOR
Box 2760, MIDLAND, TX 79702-2760
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1440' FNL E 860' FWL SEC 6 23 S 31 E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: 1787' FSL E 860' FWL SEC 31 22 S 31 E
16. REPORT APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON *

(other) *Run 938 CSO*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

DRUG. 12 1/4" HOLE TO 3705' - 2-18-82.

RAN 87 JTS, 9⁵/₈" 36# K-55 LTC C56. SET @ 3705'

CEMENT W/ 1800 SX PACESETTER LITE W/ ADDITIVES TAKED W/ 250
SX CLASS "C" W/ ADDITIVES CIRC 360 SX. PLUG DOWN @ 6:30

AM 2-18-82 FLOAT AHEAD OK. WOC 23 #AS.

2-21-82 DRLG. FLOAT & TESTED TO 1000 PSI OK, DRLG. CEMENT &
SHAPE TESTED TO 1000 PSI OK. DRLG 8 3/4" HOLE.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE _____

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY

ROGER A. CHAPMAN

TITLE

DATE _____

FEB 26 1982

* See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY
ROSWEEL, NEW MEXICO