

UNITED STATES Artesia, NM 88210

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ~~RENEWED~~

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

JUN 1 1982

2. NAME OF OPERATOR

O. C. D.

PERRY R. BASS

ARTESIA OFFICE

3. ADDRESS OF OPERATOR

P.O. Box 2760 Midland, TX. 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1440' FNL 860' FNL UNIT E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) 7" CSG.

5. LEASE

NM 02887-D

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

JAMES RANCH UNIT

8. FARM OR LEASE NAME

JAMES RANCH UNIT

9. WELL NO.

13

10. FIELD OR WILDCAT NAME

WILDCAT UNIT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 6 T23S, R31E

12. COUNTY OR PARISH 13. STATE

EDDY

NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3308.5' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

DRLG. 8 3/4" HOLE TO 11,580' 5-3-82

RAN 58 JTS. 7" 26# 5-95 LTFC CSG, 95 JTS. 7" 23# 5-95 LTFC CSG. 1 JT. 7" FULL OPENING CEMENTER, 89 JTS. 7" 26# K-55 LTFC CSG. 26 JTS. 7" 23# N-80 LTFC CSG. CEMENTED W/ 100 SX PACESSETTER LITE CLASS "H" W/ ADDITIVES, 300 SX CLASS "H" W/ ADDITIVES PLUG DOWN 1:00 PM CDST 5-3-82. DID NOT BUMP PLUG, FLOAT HELD. TEST BOP W/ YELLOW JACKET, DRLG CEMENT 11,398' TO 11,580' TEST CSG. SEAT TO 1000 PSI OK COMMENCED DRLG 6 1/8" HOLE 5-5-82. NOTE: WOC & PARTS 42 HAS.

Subsurface Safety Valve: Manu. and Type N/A

18. I hereby certify that the foregoing is true and correct

SIGNED R.C. Schenck

TITLE Lithol. Clerk

DATE

MAY 12 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

