

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
Perry R. Bass
3. ADDRESS OF OPERATOR
P. O. Box 2760, Midland, Texas. 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1440' FNL & 860' FWL Unit Letter E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: 1787' FSL & 860' FWL Sec 31 T22S R31E
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
- | | | |
|----------------------|--------------------------|--------------------------|
| TEST WATER SHUT OFF | ☐ | ☐ |
| FRACTURE TREAT | ☐ | ☐ |
| SHOOT OR ACIDIZE | ☐ | ☐ |
| REPAIR WELL | ☐ | ☐ |
| PULL OR ALTER CASING | ☐ | ☐ |
| MULTIPLE COMPLETE | ☐ | ☐ |
| CHANGE ZONES | ☐ | ☐ |
| ABANDON* | ☐ | ☐ |
- (other) Logging & 5" Liner

5. LEASE
NM 02887-D
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
James Ranch Unit
8. FARM OR LEASE NAME RECEIVED
James Ranch Unit
9. WELL NO.
13 OCT 18 1982
10. FIELD OR WILDCAT NAME
Wildcat O. C. D.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 6, T23S, R31E
12. COUNTY OR PARISH Eddy 13. STATE New Mexico
14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3308.5' GL



OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-25-82 Logging-Ran Schlumberger DLL & BHC.
Gearhart-CDL-CNS, DLL.
7-26-82 Ran 98 JTS. 5" 18# P-110 FL4S CSG. & BOT hanger
Top of Liner @ 11,253'. Western Cemented W/650 sx Class "H"
w/additives plug down @ 7:30 pm. CDT. floats held ok. Reversed
out 180 sx cement.
7-27-82 WOC 14 3/4 Hrs. pressured liner top to 1000 psi held ok.
Liner set @ 15,078'. Rig released @ 12:00 midnight.
7-30-82 Wait on completion.

Subsurface Safety Valve: Manu. and Type N/A Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. C. Hartman TITLE Sr. Prod. Clerk DATE 8-6-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY DAVID R. GLASS TITLE DATE

CONDITIONS OF APPROVAL OCT 15 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.