

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTEZIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator WA Moncrief Jr		Lease crooked Creek A St Com		Well # 1	
Location of Well	Unit 1980S 660E I	Section 2	Township 24	Range 24	County Eddy
Drilling Contractor	Kenai #21		Type of Equipment Rotary		

* Witness Co. man L. V. (Nick) Nichols
APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	48# H40 ST+C		428'	400 SX Circ
11 1/2	8 5/8	32# K-SS ST+C		2700	1000 SX Circ
7 7/8	4 1/2	11.6# N-80 LT+C		10,700	500 SX

Casing Data:

Surface joints of 8 5/8" inch 32 # Grade J-SS
(Approved) (Rejected)

Inspected by M. S. date 2/15/82

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required

Type of Shoe used guide Float collar used yes Btm 3 jts welded yes

TD of hole 2700' Set 2700' Feet of 8 5/8" Inch 32 # Grade J-SS

New-used csg. @ 2700' with 200 2%u sacks neat cement around shoe
+ 900 sax Hal. lite additives (10# gel., 1/4# floccle)

Plug down @ 4:30 (AM) (PM) Date 1/16/82

Cement circulated yes No. of Sacks 170 SX

Cemented by Halliburton Witnessed by Mike Stullfield

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks:

Centralizers @ 2660'-2620'-2580'

Full returns to TD.