NM OIL COMMISSION Drawer DD

Form Approved. Budget Bureau No. 42-R1424

RECEIVED BY

JUL 16 1985

UNITED STATES 12, NM 88210 DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

5. LEASE NM-40659

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Ο.	C.	SUNDRY	NOTICES
ARTES	A	OFFICE	NOTICES

SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas v	Pure Gold "D" Federal
well well other	9. WELL NO.
2. NAME OF OPERATOR	11
Pogo Producing Company	19 FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	West Sand Dunes Mororw
P.O. Box 10340 Midland, Texas 79702	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Sec. 28, T-23-S, R-31
AT SURFACE: 1980' FNL & 660' FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Eddy New Mexico
1980' FNL & 660' FWL	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3350.2' Ground
TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/4/85 - TD 4170'. MW 10#

6 1/4 Hrs. Drlq

2 Hrs. Svc rig hookup fluid caliper & circ hole clean.

2 3/4 Hrs. Svy & MOH LD DC no correction.

8 Hrs. Ran 18 jts 802.90' 13 3/8" 68# S-80 ST&C + 50 jts 2144.58' 61# K-55 ST&C R3 shoe 1.08', FC 1.42' total string 4176.05' w/cent on 1,3,5,7,9th jts shoe + 1 jt FC + 1 jt thrd lkd.

1 Hr. Circ capacity of csg

2 1/2 Hrs. Shoe @ 4170' & FC @ 4126' Howco cmtd w/3000 sxs Howco Lt w/15# salt & 1/4# flocele per sx avg wt 13.2# followed w/500 sxs C1 C w/3# salt avg wt 14.8 cmt circ 375 sxs CIP @ 3:30 am MDT 7/4/85.

1 1/2 Hrs. WOC.

Subsurface Safety Valve: Manu. and Type	CONTINUED ON ATTACHED	SHEET Set @ Ft.
18. I hereby certify that the foregoing is true and		
SIGNED SIGNED STORES	Petroleum Engineerate	7/8/85
(This s	pace for Federal or State office use)	
APPROVED BY ACCEPTED FOR RECORD. CONDITIONS OF APPROVAL, IF-ANY: HICK	TITLE DA	те

JUL 12 1985