

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 149
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator HNG Oil Company		Lease Baldridge Canyon 5 St Cam #1		Well #	
Location of Well	Unit 1880S 660W L	Section 5	Township 24	Range 25	County Eddy
Drilling Contractor Parker Drly Co			Type of Equipment Rotary		

*Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	48#		400'	700 SX Circ
12 1/4	9 5/8	36#		3100'	1500 SX Circ
8 1/2	5 1/2 + 4 1/2	17# + 15.5#		11,500'	850 SX

Casing Data:

Surface _____ joints of _____ inch _____ # Grade **K-55-P110**
(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole **12 1/4"** Size of Casing **9 5/8"** Sacks cement required _____

Type of Shoe used **guide** Float collar used **insert** Btm 3 jts welded **yes**

TD of hole **3070'** Set **3070'** Feet of **9 5/8"** Inch **47** # Grade **K-55-P110**

New **used** csg. @ **3070'** with **700 2#** sacks neat cement around shoe
+ **1175** sax **H/L** additives **(270cc 1/2# floreal)**

Plug down @ **4:00** (AM) (PM) Date **4/1/82**

Cement circulated **Yes** No. of Sacks **700 SX**

Cemented by **Halliburton** Witnessed by **Mike Stullfield**

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

Full returns to TD

No centralizers or baskets

last daily break @ 2970-3000'