STALE OF NEW MEXICO

HOT AND WINNERALS DE	CPAH	INI
40. 07 COPIES SECCIVED		
DISTRIBUTION		
SANTA FE	V	
FILZ	V	V
V.3,G.3,		
LAND OFFICE		_
0.000		

CONDITIONS OF APPROVAL, IF ANY:

OIL CONSERVATION DIVIAL_EIVED

Farn	0-1	03	
Rev's	ed	19-	1 -

	P. O. BOX 20	88		Revised 10-1
PILZ V V	SANTA FE, NEW ME	** 1982 - 3150 1 5 1982	7	
U.S.G.S.		5 · · · · · · · · · · · · · · · · · · ·	State X	Fae
DERATOR		O. C. D.	5. State Oil & Gas	Lease No.
		ARTESIA. OFFICE	LG-467	~~~~~~
	CES AND REPORTS ON WELL DRILL ON TO DEEPEN ON PLUG BACK I THINK I TO DEEPEN ON PLUG BACK I THINK I THE PROPERTY OF THE PROPERT	O A DIFFERENT RESERVOIR,		
OIL GAS X OTHER	-		7. Unit Agreement	Nume
Name of Operator Amoco Production Company	ı i/		8. Farm or Lease	_
. Address of Operator	· · · · · · · · · · · · · · · · · · ·		State DS	Gas Com
P. O. Box 68, Hobbs, N.	M. 88240]	
. Location of Well	د د ا		10. Field and Poo	
UNIT LETTER	FEET FROM THE South	INE AND 1980 FEET FAC	Wildcat M	11111111111111111111111111111111111111
	4 TOWNSHIP 23-S			
	15. Elevation (Show whether DF,		12. County	
		3 GL	Eddy	<u> </u>
Check Appropr	iate Box To Indicate Natu	-	Ither Data NT REPORT OF:	
	J. 13.			
PERFORM REMEDIAL WORK	PLUG AND ASANDON RE	MEDIAL WORK		NG CASING
TEMPORAHILY ASANDON	ا است	MMENCE DRILLING OPNS.	PLUG A	THEMMOCHAGA DE
PULL OR ALTER CASING	CHANGE PLANS	OTHER Status R	Report	····
	— l			
OTHER				
	(Clearly state all pertinent details,	and give pertinent dates, includi	ng estimated date of s	tarting any prope
17. Describe Proposed or Completed Operations	Ran DST #1. Results /ft. S-95 casing set cks class H with .4% I Drilled out cement. t to 6-1/2" and resume	s attached. Drilled at 9344'. Cemented Halad 4. Circulated Pressure tested casi ed drilling. Drilled	to TD of 9344 with 1800 sac 165 sacks of ing to 800 PSI	ks
Drilled to TD of 7418'. Ran 7-5/8" 39 & 33.7 lb class H lite and 200 sa cement. WOC 18 hours. Tested O.K. Reduced bi	Ran DST #1. Results /ft. S-95 casing set cks class H with .4% I Drilled out cement. t to 6-1/2" and resume	s attached. Drilled at 9344'. Cemented Halad 4. Circulated Pressure tested casi ed drilling. Drilled	to TD of 9344 with 1800 sac 165 sacks of ing to 800 PSI	ks
Drilled to TD of 7418'. Ran 7-5/8" 39 & 33.7 lb class H lite and 200 sa cement. WOC 18 hours. Tested O.K. Reduced bi	Ran DST #1. Results /ft. S-95 casing set cks class H with .4% I Drilled out cement. t to 6-1/2" and resume	s attached. Drilled at 9344'. Cemented Halad 4. Circulated Pressure tested casi ed drilling. Drilled	to TD of 9344 with 1800 sac 165 sacks of ing to 800 PSI	ks
Drilled to TD of 7418'. Ran 7-5/8" 39 & 33.7 lb class H lite and 200 sa cement. WOC 18 hours. Tested O.K. Reduced bi	Ran DST #1. Results /ft. S-95 casing set cks class H with .4% I Drilled out cement. t to 6-1/2" and resume	s attached. Drilled at 9344'. Cemented Halad 4. Circulated Pressure tested casi ed drilling. Drilled	to TD of 9344 with 1800 sac 165 sacks of ing to 800 PSI	ks
7. Describe Proposed or Completed Operations work) SEE RULE 1103. Drilled to TD of 7418'. Ran 7-5/8" 39 & 33.7 lb class H lite and 200 sa cement. WOC 18 hours. Tested O.K. Reduced bi	Ran DST #1. Results /ft. S-95 casing set cks class H with .4% I Drilled out cement. t to 6-1/2" and resume	s attached. Drilled at 9344'. Cemented Halad 4. Circulated Pressure tested casi ed drilling. Drilled	to TD of 9344 with 1800 sac 165 sacks of ing to 800 PSI	ks
Drilled to TD of 7418'. Ran 7-5/8" 39 & 33.7 lb class H lite and 200 sa cement. WOC 18 hours. Tested O.K. Reduced bi	Ran DST #1. Results /ft. S-95 casing set cks class H with .4% I Drilled out cement. t to 6-1/2" and resume	s attached. Drilled at 9344'. Cemented Halad 4. Circulated Pressure tested casi ed drilling. Drilled	to TD of 9344 with 1800 sac 165 sacks of ing to 800 PSI	ks
Drilled to TD of 7418'. Ran 7-5/8" 39 & 33.7 lb class H lite and 200 sa cement. WOC 18 hours. Tested O.K. Reduced bi Ran DST #2. Results at	Ran DST #1. Results /ft. S-95 casing set cks class H with .4% I Drilled out cement. t to 6-1/2" and resume tached. Resumed dril	s attached. Drilled at 9344'. Cemented Halad 4. Circulated Pressure tested casi ed drilling. Drilled ling.	to TD of 9344 with 1800 sac 165 sacks of ing to 800 PSI	ks
Drilled to TD of 7418'. Ran 7-5/8" 39 & 33.7 lb class H lite and 200 sa cement. WOC 18 hours. Tested O.K. Reduced bi	Ran DST #1. Results /ft. S-95 casing set cks class H with .4% I Drilled out cement. t to 6-1/2" and resume	s attached. Drilled at 9344'. Cemented Halad 4. Circulated Pressure tested casi ed drilling. Drilled ling.	to TD of 9344 with 1800 sac 165 sacks of ing to 800 PSI	ks
Drilled to TD of 7418'. Ran 7-5/8" 39 & 33.7 lb class H lite and 200 sa cement. WOC 18 hours. Tested O.K. Reduced bi Ran DST #2. Results at	Ran DST #1. Results /ft. S-95 casing set cks class H with .4% I Drilled out cement. t to 6-1/2" and resume tached. Resumed dril	s attached. Drilled at 9344'. Cemented Halad 4. Circulated Pressure tested casi ed drilling. Drilled ling.	to TD of 9344 with 1800 sac 165 sacks of ing to 800 PSI	ks
Drilled to TD of 7418'. Ran 7-5/8" 39 & 33.7 lb class H lite and 200 sa cement. WOC 18 hours. Tested O.K. Reduced bi Ran DST #2. Results at	Ran DST #1. Results /ft. S-95 casing set cks class H with .4% I Drilled out cement. t to 6-1/2" and resume tached. Resumed dril	s attached. Drilled at 9344'. Cemented Halad 4. Circulated Pressure tested casi ed drilling. Drilled ling.	to TD of 9344 with 1800 sac 165 sacks of ing to 800 PSI	ks
Drilled to TD of 7418'. Ran 7-5/8" 39 & 33.7 lb class H lite and 200 sa cement. WOC 18 hours. Tested O.K. Reduced bi Ran DST #2. Results at	Ran DST #1. Results /ft. S-95 casing set cks class H with .4% I Drilled out cement. t to 6-1/2" and resume tached. Resumed dril	s attached. Drilled at 9344'. Cemented Halad 4. Circulated Pressure tested casied drilling. Drilled ling.	to TD of 9344 with 1800 sac 165 sacks of ing to 800 PSI	ks
Drilled to TD of 7418'. Ran 7-5/8" 39 & 33.7 lb class H lite and 200 sa cement. WOC 18 hours. Tested O.K. Reduced bi Ran DST #2. Results at	Ran DST #1. Results /ft. S-95 casing set cks class H with .4% I Drilled out cement. t to 6-1/2" and resume tached. Resumed drill 1-DMF 1-W. STAFFO	s attached. Drilled at 9344'. Cemented Halad 4. Circulated Pressure tested casied drilling. Drilled ling.	to TD of 9344 with 1800 sac 165 sacks of ing to 800 PSI	ks