

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P.O. BOX 2088

RESERVED BY NEW MEXICO 87501

Form C-103
Revised 10-1-

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator HNG OIL COMPANY	8. Farm or Lease Name Faulk 32 Com.
3. Address of Operator P. O. Box 2267, Midland, Texas 79702	9. Well No. 1
4. Location of Well UNIT LETTER I 1940 FEET FROM THE south LINE AND 660 FEET FROM THE east LINE, SECTION 32 TOWNSHIP 22S RANGE 28E N.M.P.M.	10. Field and Pool, or Wildcat Wildcat (See Below)
15. Elevation (Show whether DF, RT, GR, etc.) 3033.3' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Plug back from Morrow to Atoka to Strawn

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-16-82 - Perforated Morrow 12347 - 12497

8-20-82 - Squeezed with 50 sacks Class H Cement; tested squeeze to 7000 psi.

8-21-82 - Perforated Morrow 12063 - 12135

7-20-83 - Set a 4-1/2" Otis WB Packer with plug in nipple at 11,750' and test.

7-22-83 - Perforated Atoka 11,358 to 11,371.

11-20-84 - Squeezed Atoka Perfs with 35 sacks Class H Cement. Tested squeeze to 6000 psi.

11-22-84 - Perforated Strawn 11,133 to 11,138.

Propose to squeeze Strawn with 25 sacks Class H cement. Spot 35 sacks from 8500 to 8350 feet, and 35 sacks from 6500 to 6350 feet. Test Bone Springs 6040 to 6080 feet.

Post FD-2
6-21-85
P & A Man

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Betty Gildon Betty GildonTITLE Regulatory AnalystDATE 6/13/85Original Signed By
Les A. ClementsAPPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY: Supervisor District 11

TITLE _____

DATE JUN 17 1985