

2/5F

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Drawer DD  
Artesia, NM

5. LEASE  
88210  
NM 29414-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ridge Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Baldrige Canyon Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

sec. 23, T24S, R24E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

4639 GD, 4662 KB

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil well ☐ gas well ☒ other

OCT 7 1982

2. NAME OF OPERATOR

W.A. Moncrief, Jr.

3. ADDRESS OF OPERATOR

400 Metro Bldg. Midland, Texas 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 487'FNL and 1620'FWL section 23

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐


MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) casing test and cement job

SUBSEQUENT REPORT OF:



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

(1.) Well was spudded at 5 pm 7/17/82

(2.) Operator set 13 3/8" 48# H-40 ST&C casing at 440 rotary measurements (433 casing talley) and cemented w/400 sax class "c" w/10# gilsomite & 1/2# Flo cel per sack followed by 200 sax class "c" w/2% CaCl 7/19/82. Cement circulated. Cement job was witnessed by Federal man. woc 12hrs, Tested casing to 1000# for 20 minutes. Held ok.

(3.) Operator set 8 5/8" 32# K-55 ST&C casing at 2988' and cemented w/900 sax Howco lite w/10# gilsomite per sack followed by 200 sax class "c" w/2% CaCl 7/29/82 and found top of cement at 1460'. Cemented through 1" Kobe tubing from the surface in 10 stages w/900 sax calss "c" w/2-3% CaCl 7/29, 7/30 and 7/31/82. Cement circulated on last stage w/PD at 6:15 AM 7/31/82. All stages of cement job were witnessed by either Mr. Coke or Mr. Jones, woc 18 hrs. Tested casing and BOP to 1600# for 15 minutes. Held ok.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dewey E. Thornton

TITLE Exploration Manager

DATE 8/9/82

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 5 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side