

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-7

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.O.S.	
LAND OFFICE	
OPERATOR	☒

OCT 19 1982

O. C. D.

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
LG-589

SUNDARY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name State "MS" Gas Com
3. Address of Operator P. O. Box 68, Hobbs, NM 88240	9. Well No. 1
4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 12 TOWNSHIP 24-S RANGE 27-E NMPM.	10. Field and Pool, or wildcat Und. Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3092. GL	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☒ Drilling

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to total depth 9584'. Ran 7-5/8" 39 lb./ft. and 33.7 lb./ft. S-95 on 8-30-82. Cemented first stage with 550 SX class H lite. Tail-in with 400 SX class H. Circulated 200 SX in 6 hr. Cemented second stage with 1325 SX class H lite and 400 SX of Class H. Circulated 100 SX. WOC 18 hr. Pressure test casing 1500 psi for 30 min. OK. Reduced hole to 6-1/2 and resumed drilling. Drilled to a total depth of 12,261'. Ran 5.5" 19.81 lb./ft. S-95 liner on 9-30-82. Set at 12,258'. Top of liner at 9168'. Cemented with 375 SX class H cement and additives. WOC 18 hrs. Tested liner 1500 psi for 30 min., held O.K. Reduced bit to 4-3/4" and resumed drilling.

0+4-NMOCD,A 1-HOU 1-W. Stafford, HOU 1-CMH 1-HNG Oil -Mid.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles M. Herring TITLE Assist. Admin. Analyst

DATE 10-6-82

Original Signed By
Leslie A. Clements

APPROVED BY Supervisor District II
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE OCT 20 1982