

#1 OGDEN
WELL COMPLETION OR RECOMPLETION REPORT AND LOG
ATTACHMENT

Perforation Record (Interval, size and number)	32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.	
	DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
12,664'-12,672', 8', 32 holes.	12,664'-12,672'	2000gal 7 1/2% Morrowflo.
12,530'-12,534', 4', 16 holes.	12,530'-12,534' & 12,561'-12,565'	2000gal 7 1/2% Morrowflo.
12,561'-12,565', 4', 16 holes.	12,360'-12,377'	6000gal 7 1/2% Morrowflo. Squeeze w/
12,360'-12,377', 17', 68 holes.		100sx Class "H", spot 120gal 10% MSA.
12,230'-12,232', 2', 5 holes.	12,230'-12,232', 12,236'-12,238'	
12,236'-12,238', 2', 5 holes.	12,242'-12,254' & 12,327'-12,332'	4000gal 7 1/2% Morrowflo.
12,242'-12,254', 2', 5 holes.	12,310'-12,316' & 12,334'-12,338'	2000gal 7 1/2% Morrowflo.
12,327'-12,332', 5', 11 holes.	12,230'-12,232', 12,236'-12,238'	Frac w/2000gal 7 1/2% Morrowflo;
12,310'-12,316', 6', 13 holes.	12,242'-12,254', 12,327'-12,332'	19,000gal glid wtr & CO ₂ ; 12,500#
12,334'-12,338', 4', 9 holes.	12,310'-12,316' & 12,334'-12,338'	20-40 sd.