

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN THE FORM OF A PERMIT (Other instructions on reverse side) NM 88410 Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" (Form 9-332).)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	5. LEASE DESIGNATION AND SERIAL NO. NM-54398
2. NAME OF OPERATOR The Eastland Oil Company	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Drawer 3488, Midland, Texas	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1830' FNL and 2140' FWL	8. FARM OR LEASE NAME Fortson Federal Com.
14. PERMIT NO.	9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 2958' GR, 2975' RT	10. FIELD AND POOL, OR WILDCAT Malaga (Morrow)
	11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec. 12, T24S, R28E
	12. COUNTY OR PARISH Eddy
	13. STATE New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐ Casing setting	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 12-1/4" hole to 2680' in lime and shale at 9:30 a.m., 11-16-82. Ran 65 joints 36#, K-55, #1, 9-5/8" csg., 2663', set at 2680', with float and guide shoe. Cemented w/1000 sacks Halliburton Lite w/1/4# Flocele per sack and 2% CaCl₂ followed by 400 sacks Class C with 2% CaCl₂. POB @ 7:30 p.m., 11-16-82. Circulated out 300 sacks excess cement. Bumped plug w/1200 psi. Checked float - O.K. Nippled up well head and BOP stack. Tested BOP blind and pipe rams to 5000 psi and Hydril to 3000 psi with yellowjacket testers. Drilled out float and 42 feet cement. Started drilling formation at 11:00 p.m. 11-18-82 with 8-1/2" hole.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass

TITLE Vice President-Production

DATE 11-19-82

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY (ORIG. SGD) DAVID R. GLASS

CONDITIONS OF APPROVAL NOV 24 1982

TITLE

DATE

U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.