

EQUIPMENT & HOLE DATA

FORMATION TESTED: BONE SPRINGS

NET PAY (ft): _____

GROSS TESTED FOOTAGE: 110.0

ALL DEPTHS MEASURED FROM: KELLY BUSHING

CASING PERFS. (ft): _____

HOLE OR CASING SIZE (in): 7.875

ELEVATION (ft): 3218

TOTAL DEPTH (ft): 5750.0

PACKER DEPTH(S) (ft): 5634, 5640

FINAL SURFACE CHOKE (in): 0.375

BOTTOM HOLE CHOKE (in): 0.750

MUD WEIGHT (lb/gal): 10.00

MUD VISCOSITY (sec): 28

ESTIMATED HOLE TEMP. (°F): _____

ACTUAL HOLE TEMP. (°F): 111 @ 5746.0 ft

TICKET NUMBER: 25448000

DATE: 12-9-82 TEST NO: 2

TYPE DST: OPEN HOLE

HALLIBURTON CAMP: ARTESIA

TESTER: STAN MC KEE

WITNESS: PERRY BRASHER

DRILLING CONTRACTOR: DELTA 60

FLUID PROPERTIES FOR RECOVERED MUD & WATER

SOURCE	RESISTIVITY	CHLORIDES
MUD PIT	0.070 @ 64 °F	179000 ppm
TOP RECOVERY	0.060 @ 64 °F	200000 ppm
MIDDLE RECOVERY	0.060 @ 64 °F	200000 ppm
BOTTOM RECOVERY	0.060 @ 84 °F	200000 ppm
	@ °F	ppm
	@ °F	ppm

SAMPLER DATA

Pstlg AT SURFACE: 575

cu.ft. OF GAS: 4.35

cc OF OIL: 0

cc OF WATER: 1950

cc OF MUD: 0

TOTAL LIQUID cc: 1950

HYDROCARBON PROPERTIES

OIL GRAVITY (°API): _____ @ _____ °F

GAS/OIL RATIO (cu.ft. per bbl): _____

GAS GRAVITY: _____

CUSHION DATA

TYPE AMOUNT WEIGHT

RECOVERED:

1658 FEET OF RECOVERY - GAS CUT BRINE

MEASURED FROM
TESTER VALVE

REMARKS:

ALL DEPTHS MEASURED 22 FEET ABOVE GROUND LEVEL.
NO READINGS AVAILABLE ON B.T. # 1113 - CHART TOO FAINT TO READ.