

MEASURED DEPTH	INCL. ANGLE	HOLE DIRECTION	COURSE LENGTH	TRUE VERTICAL DEPTH	VERTICAL SECTION	N/S	feet	E/W	RECTANGULAR COORDINATES	C L O S U R E	DIRECTION	SEVERITY	DG/100FT
FEET	DEGS.	DEGS.	FEET	FEET	FEET						DEGS.		
7400.00	1.50	S 51.00 W	100.00	7396.84	-33.43	33.43	N	64.24	E	72.41	N 62.50 E		.10
7500.00	1.75	S 48.00 W	100.00	7496.80	-31.59	31.59	N	62.08	E	69.65	N 63.03 E		.26
7600.00	1.75	S 51.00 W	100.00	7596.75	-29.60	29.60	N	59.76	E	66.69	N 63.64 E		.09
7700.00	2.00	S 48.00 W	100.00	7696.70	-27.48	27.48	N	57.27	E	63.52	N 64.36 E		.27
7800.00	1.50	S 37.00 W	100.00	7796.65	-25.23	25.23	N	55.21	E	60.70	N 65.44 E		.60
7900.00	1.25	S 33.00 W	100.00	7896.62	-23.26	23.26	N	53.83	E	58.65	N 66.62 E		.27
8000.00	1.25	S 34.00 W	100.00	7996.60	-22.16	22.16	N	52.03	E	56.56	N 66.93 E		1.08
8100.00	1.00	S 74.00 W	100.00	8096.58	-21.79	21.79	N	50.11	E	54.64	N 66.50 E		.32
8200.00	2.00	S 70.00 W	100.00	8196.54	-20.98	20.98	N	47.62	E	52.04	N 66.22 E		1.00
8300.00	2.50	S 71.00 W	100.00	8296.47	-19.67	19.67	N	43.92	E	48.12	N 65.87 E		.50
8380.00	3.00	S 73.00 W	80.00	8376.37	-18.48	18.48	N	40.27	E	44.31	N 65.34 E		.64
KOP (8430' MD - 3.0 - 573W)													
8410.00	5.00	S 43.00 W	30.00	8406.30	-17.39	17.39	N	38.52	E	42.26	N 65.70 E		9.44
8502.00	7.00	S 14.00 W	92.00	8497.79	-9.03	9.03	N	33.98	E	35.15	N 75.12 E		3.88
8594.00	10.25	S 07.00 W	92.00	8588.74	4.53	4.53	S	31.46	E	31.79	S 81.80 E		3.71
8686.00	11.50	S 05.00 W	92.00	8679.08	21.79	21.79	S	29.65	E	36.80	S 53.68 E		1.42
8778.00	12.50	S 02.00 W	92.00	8769.07	40.88	40.88	S	28.48	E	49.82	S 34.86 E		1.28
8871.00	14.25	S 02.00 E	93.00	8859.55	62.39	62.39	S	28.48	E	68.58	S 24.53 E		2.13
8963.00	15.50	S 05.00 E	92.00	8948.46	85.96	85.96	S	29.92	E	91.02	S 19.19 E		1.60
9055.00	16.00	S 10.00 E	92.00	9037.01	110.71	110.71	S	33.18	E	115.58	S 16.68 E		1.57
9147.00	17.25	S 12.00 E	92.00	9125.16	136.55	136.55	S	38.20	E	141.79	S 15.63 E		1.49
9239.00	17.50	S 15.00 E	92.00	9212.96	163.26	163.26	S	44.62	E	169.24	S 15.28 E		1.01
9332.00	18.25	S 17.00 E	93.00	9301.47	190.70	190.70	S	52.48	E	197.79	S 15.38 E		1.04
9424.00	19.00	S 20.00 E	92.00	9388.65	218.56	218.56	S	61.81	E	227.13	S 15.79 E		1.32
9516.00	19.75	S 22.00 E	92.00	9475.44	247.05	247.05	S	72.74	E	257.54	S 16.40 E		1.09
9608.00	21.00	S 25.00 E	92.00	9561.68	276.42	276.42	S	85.51	E	289.34	S 17.19 E		1.77